



### Technical Characteristics

|                             |   |
|-----------------------------|---|
| Resistive Amperes (AC1)     | 20A   |
| Inductive Amperes (AC3)     | 9A  |
| Contactor Type              | Non-Reversing   |
| Certifications              | UL Listed (E164862 / NLDX) - CSA Certified (LR43364 3211 04) - IEC Rated (60647-4) - CE Marked - RoHS Compliant |
| Marketing Trade Name        | TeSys   |
| Mounting Style              | 35mm DIN Rail   |
| Maximum Voltage Rating      | 600 Vac   |
| Coil Voltage                | 24Vac@50/60Hz   |
| Horsepower Rating (1-Phase) | 0.5HP@115Vac - 1HP@230Vac   |
| Number of Poles             | 3-Pole (3 NO)   |
| Horsepower Rating (3-Phase) | 2HP@200/230Vac - 5HP@460Vac - 7.5HP@575Vac  |
| Coil Voltage Code           | B7  |
| Coil Consumption Sealed     | 7.5 VA  |
| Coil Consumption Inrush     | 70 VA   |
| Power Terminal Torque       | 15 lb-in (1.7 Nm)   |
| Terminal Type               | Screw Clamp   |
| Control Terminal Torque     | 15 lb-in (1.7 Nm)   |
| Type                        | TeSys D   |
| Power Wire Size             | #10 to #18 AWG  |
| Control Wire Size           | #10 to #18 AWG  |
| Weight                      | 0.71 lbs (0.32 kg)  |

### Shipping and Ordering

|                   |   |
|-------------------|---|
| Category          | 22345 -   |
| Discount Schedule | I12   |
| GTIN              | 00785901206927  |
| Package Quantity  | 1   |
| Weight            | 0.77 lbs.   |
| Availability Code | Stock Item: This item is normally stocked in our distribution facility. |
| Returnability     | Y   |
| Country of Origin | FR  |

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.

Generated: 10/14/2009 10:55:25