

**NEW**

# "3 in 1" Combi-Terminal Switch



*"3 in 1" combi-terminals function as .250 Quick Connect, Solder Lug or Screw Terminals.*

In an effort aimed at reducing distributor inventory and increasing flexibility, Carling Technologies is pleased to introduce our new "Combi" terminal switches. These terminals function as both a .250 Quick Connect and Solder Lug terminal. In addition a screw and saddle clamp are included to provide a Screw Terminal option. This new offering is available on all full size Carling one to three pole rocker and toggle switches, and is a direct replacement for the discontinued Eaton 7800 series toggles with similar terminations.

Additional features include:

- UL, CSA approved
- Available with all circuits
- Parts provided in individual polybags
- Eliminates the need to stock three separate terminal configurations
- Available with standard #5 rating (10A 250VAC 15A 125 VAC 3/4 HP 125-250 VAC)
- Additional ratings to 20A 125 VAC available (consult factory for specifics)
- Full Choice of actuator colors and styles
- No additional lead-time

Product Availability:

- Samples and production orders are available

Product Bulletin #87R-1 April 18, 2002

For additional information on the "3 in 1" Combi-Terminal Switch, please contact a Carling Technologies Technical Customer Service Rep:

phone	(860) 793-9281
fax	(860) 793-9231
email	sales@carlingtech.com
internet	www.carlingtech.com
mail	Carling Technologies, Inc. 60 Johnson Avenue Plainville, CT 06062-1177



**Carling Technologies™**  
Innovative Designs. Powerful Solutions.

## "3 in 1" Combi-Terminal Toggle Switch Ordering Scheme

### SINGLE POLE IN SINGLE POLE BASE

**2FA52** - **73**

<sup>1</sup>  
Base Part Number

<sup>2</sup>  
Actuator

#### 1 BASE PART NUMBER: SERIES / SINGLE POLE / CIRCUITRY / RATING 5 / TERMINATION

RATING 5 = 10A 250 VAC, 15A 125 VAC, 3/4 HP 125-250 VAC<sup>2</sup>  
F-Series Toggle

##### circuit<sup>1</sup>

	single pole
ON-NONE-OFF	<b>2FA52</b>
(ON)-NONE-OFF	<b>6FA5H</b>
ON-NONE-(OFF)	<b>6FA5Y</b>
ON-NONE-ON	<b>2FB52</b>
ON-NONE-(ON)	<b>6FB52</b>
ON-OFF-ON	<b>2FC52</b>
ON-OFF-(ON)	<b>6FC5Y</b>
(ON)-OFF-(ON)	<b>6FC5H</b>

#### 2 BAT STYLE TOGGLE

unsealed	toggle length	bushing length
<b>73</b>	0.687	0.465
<b>E3</b>	2.000	0.465
sealed	toggle length	bushing length
<b>78</b>	0.687	0.465
<b>E8</b>	2.000	0.465

### SINGLE AND DOUBLE POLE IN DOUBLE POLE BASE

**2GK57** - **73**

<sup>1</sup>  
Base Part Number

<sup>2</sup>  
Actuator

#### 1 BASE PART NUMBER: SERIES / DOUBLE POLE BASE/ CIRCUITRY / RATING 5 / TERMINATION

RATING 5 = 10A 250 VAC, 15A 125 VAC, 3/4 HP125-250VAC<sup>2</sup>  
G-Series Toggle

##### circuit<sup>1</sup>

	single pole	double pole
ON-NONE-OFF	<b>2GA57</b>	<b>2GK57</b>
(ON)-NONE-OFF	<b>6GA5H</b>	<b>6GK5H</b>
ON-NONE-(OFF)	<b>6GA5Y</b>	<b>6GK5Y</b>
ON-NONE-ON	<b>2GB57</b>	<b>2GL57</b>
ON-NONE-(ON)	<b>6GB5H</b>	<b>6GL5H</b>
ON-OFF-ON	<b>2GC57</b>	<b>2GM57</b>
ON-OFF-(ON)	<b>6GC5H</b>	<b>6GM5H</b>
(ON)-OFF-(ON)	<b>6GC5Y</b>	<b>6GM5Y</b>

#### 2 TOGGLE

##### bat style

unsealed	toggle length	bushing length
<b>73</b>	0.687	0.465
<b>D-3B-B</b>	0.687	0.379
sealed	toggle length	bushing length
<b>78</b>	0.687	0.465

##### paddle style

unsealed	toggle length	bushing length
<b>NBL3</b>	0.687	0.465
sealed	toggle length	bushing length
<b>NBL8</b>	0.687	0.465
<b>D-4B-B</b>	0.687	0.379

#### NOTES

Additional ratings available. Consult factory for ordering information.  
Three and four pole switches also available. Consult factory for details.

<sup>1</sup> ( ) - momentary

<sup>2</sup> Rating appropriate for usage in low voltage DC applications. For additional rating requirements, consult factory.



**Carling Technologies™**

Innovative Designs. Powerful Solutions.