

LC1K0610G7

Miniature Contactor , Non-Reversing, 3-Pole,
TeSys, Type: TeSys K



Technical Characteristics

| | |
|-----------------------------|---|
| Horsepower Rating (1-Phase) | 0.5HP@115VAC - 1.5HP@230VAC |
| Resistive Amperes (AC1) | 15A |
| Inductive Amperes (AC3) | 6A |
| Approvals | UL Listed File E164862 NLDX2 - CSA Certified File LR43364 Class 3211 04 - IEC Rated 60947 - CE Marked |
| Auxiliary Contacts | 1 N.O. |
| Horsepower Rating (3-Phase) | 1.5HP@200/230VAC - 3HP@460/575VAC |
| Marketing Trade Name | TeSys |
| Maximum Voltage Rating | 600VAC |
| Weight | 0.40 Pounds |
| Number of Poles | 3-Pole |
| Operating Voltage | 120VAC |
| Depth | 2.24 Inches |
| Mounting Type | Panel |
| Height | 2.28 Inches |
| Action | Non-Reversing |
| Terminal Type | Screw Clamp |
| Type | TeSys K |
| Width | 1.77 Inches |

Shipping and Ordering

| | |
|-------------------|---|
| Category | 22326 - Contactors, AC, Open, Non-Reversing, K-Line |
| Discount Schedule | I12 |
| GTIN | 00785901401025 |
| Package Quantity | 1 |
| Weight | 0.4 lbs. |
| Availability Code | Stock Item: This item is normally stocked in our distribution facility. |
| Returnability | Y |
| Country of Origin | FR |

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.

Generated: 09/18/2009 09:33:23