

- Long-life, ball bearing construction
- Locked rotor and polarity protection
- Silent operation
- Industry standard frames and mounting
- Meets or exceeds safety standards
- Custom cable/connector assemblies
- Sensor fans available (special order)



## AC Fans

Frame Size H x W x D mm (inches)	Model	Voltage (V)	Airflow (CFM)	Input Power (Watts)	Speed (RPM)	Noise Level (dBA)	Weight (Oz)	Construction	Guard Filter Cord
80 x 80 x 25 (3.2 x 3.2 x 1.0)	PM033-115-8025B-4	115	33	10.0	2700	33	6.8	Aluminum housing, plastic impeller, sealed ball bearing 22AWG wire leads	5508 80FP-45 5505
	PM033-230-8025B-4	230							
80 x 80 x 38 (3.2 x 3.2 x 1.5)	PM037-115-8038BT-4	115	37	12.0	2700	39	10.3	Aluminum alloy housing, plastic impeller, sealed ball bearing, terminal block	5508 80FP-45 5505
	PM037-230-8038BT-4	230							
92 x 92 x 25 (3.6 x 3.6 x 1.0)	PM040-115-9225BT-4	115	40	12.0	2400	39	8.0	Aluminum housing, plastic impeller, sealed ball bearing, terminal block	5520 92FP-45 5505
	PM040-230-9225BT-4	230							
120 x 120 x 25 (4.7 x 4.7 x 1.0)	PM053-115-1225BT-4	115	53	13.0	1900	38	11.8	Aluminum housing, plastic impeller, sealed ball bearing, terminal block	5504 5502 120FP-45 5505
	PM053-230-1225BT-4	230							
	PM080-115-1225BT-4	115							
120 x 120 x 38 (4.7 x 4.7 x 1.5)	PM080-230-1225BT-4	230	80	18.0	2300	45	11.8		
	PM115-115-1238BT-4	115	115	20.0	3000	49	18.2	Aluminum housing, plastic impeller, sealed ball bearing, terminal block	5504 5502 120FP-45 5505
PM115-230-1238BT-4	230								
172 x 150 x 38 (6.8 x 6.0 x 1.0)	PM220-115-1738BT-4	115	220	32.0	3100	52	31.0	Aluminum housing, plastic impeller, sealed ball bearing, terminal block	5506 5505
	PM220-230-1738BT-4	230							
172 x 150 x 51 (6.8 x 6.0 x 2.0)	PM238-115-1751BT-4	115	238	32.0	3100	55	33.3	Aluminum housing, plastic impeller, sealed ball bearing, terminal block	5506 5505
	PM238-230-1751BT-4	230							

## AC Radial Blowers

120 x 120 x 38 (4.8 x 4.8 x 1.5)	PMB24-115-4B PMB24-230-4B	115 230	24	20.0	2300	53	23.0	Plastic housing, plastic wheel, sealed ball bearing, 20 AWG wire leads	N/A
-------------------------------------	------------------------------	------------	----	------	------	----	------	--	-----

## Accessories

Product Type	Part Number	Fan Compatibility	Construction
Finger Guards	5514	40 mm	Nickel chrome plated wire guards, spot welded
	5516	60 mm	
	5508	80 mm	
	5520	92 mm	
	5504	120 mm	
	5506	162 mm	
Filter Guards	60FGM	60 mm	Metal mesh filter
	80FGM	80 mm	
	92FGM	92 mm	
	120FGM	120 mm	
	162FGM	162 mm	
Plastic Filter Guards	40FP-45	40 mm	Plastic filter and finger guard assembly (45PPI foam filter media)
	60FP-45	60 mm	
	80-FP-45	80 mm	
	92FP-45	92 mm	
	120FP-45	120 mm	
	162FP-45	162 mm	
Cords	5505	-	24" (straight) plug and cord for terminal block; blunt cut ends
	5505-45D	-	24" (45°) plug and cord for terminal block; blunt cut ends