

HOOK-UP WIRE

MIL-W-16878/3

TYPE D - UNCOVERED PVC


DESCRIPTION:

Stranded tinned copper, color coded.
polyvinylchloride insulation.

CHARACTERISTICS:

Temperature rating — 55°C to +105°C.
Voltage rating 3000 Volts. Resistant to acids, alkalis,
oil, flame, moisture, solvents, and fungus.

OLYMPIC NO.	TYPE DESIGNATION	CONDUCTOR SIZE	CONDUCTOR STRAND	NOM. WALL THICKNESS	NOM. O.D.
230	D-24	24	7/32	.029"	.082"
231	D-22	22	7/30	.029"	.088"
232	D-20	20	7/28	.029"	.096"
233	D-18	18	7/26	.029"	.106"
234	D-16	16	19/29	.029"	.115"
235	D-14	14	19/27	.029"	.129"
236	D-12	12	19/25	.034"	.158"
237	D-10	10	37/26	.037"	.185"
238	D-8	8	133/29	.040"	.247"
239	D-6	6	133/27	.040"	.290"

MIL-W-16878/19

TYPE D - NYLON JACKET


DESCRIPTION:

Stranded tinned copper, color coded.
.010" polyvinylchloride insulation, clear nylon
(polyamide) jacket overall.

CHARACTERISTICS:

Temperature rating — 55°C to +115°C.
Voltage rating 3000 Volts. Resistant to acids, alkalis,
oil, flame, moisture, solvents, and fungus.

OLYMPIC NO.	TYPE DESIGNATION	CONDUCTOR SIZE	CONDUCTOR STRAND	NOM. WALL THICKNESS	NOM. JACKET THICKNESS	NOM. O.D.
240	D-24	24	7/32	.029"	.004"	.090"
241	D-22	22	7/30	.029"	.004"	.096"
242	D-20	20	7/28	.029"	.004"	.104"
243	D-18	18	7/26	.029"	.004"	.114"
261	D-18	18	19/30	.029"	.004"	.115"
244	D-16	16	19/29	.029"	.005"	.125"
245	D-14	14	19/27	.029"	.005"	.139"
246	D-12	12	19/25	.034"	.005"	.168"
247	D-10	10	37/26	.037"	.006"	.197"
248	D-8	8	133/29	.040"	.009"	.265"
249	D-6	6	133/27	.040"	.010"	.310"

MIL-W-16878/4

TEFLON TYPE E - EXTRUDED


DESCRIPTION:

Single conductor stranded silver plated copper
extruded TFE Teflon insulation.

CHARACTERISTICS:


Temperature rating — 65°C to +200°C.
Voltage rating 600 Volts. Resistant to acids, alkalis,
oil, flame, moisture, solvents, and fungus.

UL Rated - 105°C

OLYMPIC NO.	TYPE DESIGNATION	CONDUCTOR SIZE	CONDUCTOR STRAND	NOM. WALL THICKNESS	NOM. O.D.
300	E-32	32	7/40	.010"	.029"
*301	E-30	30	7/38	.010"	.032"
*302	E-28	28	7/36	.010"	.036"
*303	E-26	26	7/34	.010"	.040"
*304	E-26	26	19/38	.010"	.041"
*305	E-24	24	19/36	.010"	.045"
*306	E-24	24	7/32	.010"	.044"
*307	E-22	22	19/34	.010"	.051"
*308	E-22	22	7/30	.010"	.050"
*309	E-20	20	19/32	.010"	.059"
*310	E-20	20	7/28	.010"	.058"
*311	E-18	18	19/30	.010"	.070"
*312	E-16	16	19/29	.010"	.077"
†313	E-14	14	19/27	.012"	.094"
†314	E-12	12	19/25	.012"	.113"
†315	E-10	10	37/26	.012"	.134"

* UL1213 only supplied if specified when ordering.

† Not UL recognized



*Olympic Wire and Cable Corporation
has become an industry leader in
quality electronic wire and cable.*

*With over 25 years of service, Olympic offers
a complete line of voice, data, and fibre optic
cables with an additional 2,000 items available
for immediate shipment.*

*For a solution to your wire and cable requirements,
you can count on the 'Olympic Team'.*

Olympic

WIRE & CABLE CORP.

WEBSITE:

www.olympicwire.com

EMAIL:

sales@olympicwire.com

MAIN OFFICE:

7 Madison Road
Fairfield, New Jersey 07004
Phone: 973/227-7996 Fax: 973/227-1606

HOT LINE:

800/526-2269