

# Model #: UL17CB-15

## Waber-by-Tripp Lite Power Strip - Multiple outlet strip with relocatable power tap



#### **Highlights**

9 outlets 15 ft. cord 12.5" length All metal housing 9th outlet on end panel

### Description

This W applications. I on the panel o tabs for installat electrical devices generator power. circuit breaker and attractive blue/gray color scheme. Lifetime warranty.

PLUG/OUTLETS - Input: NEMA 5-15P/Output: 9 NEMA 5-15R

ELECTRICAL - 120VAC, 50/60Hz, 15A (Requires standard NEMA 5-15R wall receptacle)

FORMAT - Corded power distribution strip

#### Applications

Offers multiple o ideal for distributing alternate waveform UPS or generator power to protected equipment.

#### Package Includes

UL17CB-15 Power Strip Warranty information Instruction manual

#### **Features**

Multi-outlet power strip offers convenient power distribution in workbench, wallmount or floor mount applications Includes

panel opposite the input line cord to accommodate large plugs with minimal blockage Lighted power switch with transparent snap-over guard to prevent accidental shutoff Keyhole mounting tabs support permanent installation on a wide variety of surfaces UL1363 (USA), cUL (Canada) 15 amp power handling capacity with circuit breaker 15 foot AC line cord Lifetime warranty

# Specifications

SYSTEM OVERVIEW	
Voltage compatibility	120VAC
Frequency compatibility	50/60 Hz
OUTPUT	
Output volt amp capacity (amps)	15A
Outlet quantity / type	9 Nema 5-15R
Outlet orientation	Single row of 8 outlets, plus a 9th outlet placed away from the rest on the panel opposite the input line cord to accommodate transformers without blocking outlets
Outlet spacing	1-8 spaced 1.625 in.
INPUT	
Input connection type	Nema 5-15P
Input cord gauge, type	14 gauge, SJT
Input cord length (ft.)	15
Input cord length (m)	4.572
Recommended Electrical Service	15A 120V
LEDS ALARMS & SWITCHES	
Switches	Lighted 2 position switch controls power to all outlets
Locking switch cover	Transparent on/off switch cover prevents accidental turn-off
PHYSICAL	
Unit Dimensions (HWD/in)	12.5 x 2.5 x 1.5
Unit Dimensions (HWD/cm)	31.75 x 6.35 x 3.8
Material of construction	Metal
Integrated keyhole mounting tabs	Keyhole mounting tabs enable mounting to a variety of surfaces
Receptacle Color	Black
AC line cord color	Black
CERTIFICATIONS	
UL1363 (Power Tap)	UL1363
cUL / CSA (Canada)	cUL
WARRANTY	
Product warranty	Lifetime