

**SEARCH OUR PRODUCTS**


aluminum electrolytic & organic semiconductor



film



power film




tantalum ceramic



TECH TOOLS



## Aluminum Electrolytic Capacitors

**+85°C Standard Axial Lead Aluminum Electrolytic Capacitors**



**Part Number: 227TTA016M**

[General Specifications \(PDF\)](#)

[Special Order Options](#)

[TTA document \(PDF\)](#)

### Electrical Specifications

**Capacitance:** 220.0  $\mu$ F

**Tolerance:** -20 %, +20 %

**Dissipation Factor:** 0.17 at 120 Hz

**ESR:** 1.281 Ohms at 20° C and 120 Hz

**Impedance:**

- and -

- and -

**Impedance Ratios:**

2.0 -25°C/20°C

6.0 -40°C/20°C

**Load Life:**

2000 Hours at 85°C with 100% of rated voltage and with 0% of rated ripple current

**Temperature Range:** -40°C to +85°C

**WVDC:** 16 volts DC

**SVDC:** 20. volts DC

**Leakage Current:**

106.0  $\mu$ A after 1 Minute

**Ripple Current:**

260.0 mA at 120 Hz and 85°C


### Physical Specifications

**Diameter (D):** 8.0 mm + 0.5 mm

**Length (L):** 16.0 mm + 1.0 mm

**Lead Wire Diameter (d):** 0.6 mm + 0.05 mm

**Lead Length:** 35mm



 **Add To Sample Cart**  
(You can always remove it later)