

## HBL7545C -- Twist-Lock Plug




2P2W, 15A 125V, L1-15P, Black & White  
Nylon

## Product Specifications

<b>Product Type</b>	 <p><b>Twist-Lock Devices</b></p>
<b>Product Item</b>	Plug
<b>Wiring Scheme</b>	2 Pole, 2 Wire Non-Grounding
<b>Amperage</b>	15A
<b>Voltage</b>	125V AC
<b>NEMA Configuration</b>	L1-15P
<b>Item Style</b>	Standard
<b>Device Color</b>	Black/White
<b>Horsepower</b>	0.5
<b>Cord Dia.</b>	.230"-.720" (5.8-18.3)
<b>Blade Holder Material</b>	Natural White Nylon
<b>Terminal Retainer Material</b>	Clear polycarbonate
<b>Housing Material</b>	Black nylon
<b>Cord Clamp Material</b>	Natural (white) nylon
<b>Blade Material</b>	Brass
<b>Terminal Clamp Material</b>	Cold rolled steel-nickel-plated


<b>Terminal Screw Material</b>	#8-32 Brass (white finish on neutral screw when used)
<b>Cord Clamp Screw Material</b>	Steel-zinc-plated
<b>Body Holding Screw Material</b>	Steel-zinc-plated
<b>Ratings</b>	Molded into face
<b>Dielectric Voltage Withstand</b>	2000V minimum
<b>Current Interrupting</b>	Certified for current interrupting at full rated current.
<b>Temperature Rise</b>	Max 30C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of .75.
<b>Cord Accommodation</b>	Round portable service cords of diameters commensurate with the device rating as defined in UL Standard 62, CSA C22.2 No. 49.
<b>Terminal Accommodation</b>	15A-#14AWG
<b>Terminal Identification</b>	Terminals identified in accordance with UL 498 (Black, White)
<b>Flammability</b>	HB or better per UL 94 or CSA 22.2 No. 0.6
<b>Operating Temperatures</b>	Maximum Continuous 75 C Minimum -40 C (w/o impact)
<b>Moisture Resistance</b>	IP20
<b>Listings</b>	UL
<b>Catalog Page</b>	<a href="#">Click here for catalog page B3</a>
<b>Hubbellnet</b>	<a href="#">Click here for Hubbellnet</a>
<b>Catalog Section</b>	<a href="#">Click here for Section-B</a>
<b>UPC Number</b>	78358517850
<b>Weight in LBs</b>	0.15



# TWIST-LOCK® Devices 2 Pole, 2 Wire Non-Grounding


15 Ampere, 125 Volts

Receptacles, INSULGRIP® Plug, Connector Body,  
Flanged Inlet and Flanged Receptacles




## Receptacles

Description	Catalog Numbers
Duplex, flush, black phenolic.	<b>HBL7540</b> -
Single, flush, black phenolic.	<b>HBL7535</b> -
Single, panel mount, 1 <sup>15</sup> / <sub>16</sub> " (49.2) centers, black phenolic.	<b>HBL7498</b> -



## Insulgrip Plug IP20 SUITABILITY

Description	Cord Dia.	Catalog Number
Black and white nylon, polarized. Multiple drive screws.	.230"-.720" (5.8-18.3)	- <b>HBL7545C</b>



## Insulgrip Connector Body IP20 SUITABILITY

Description	Cord Dia.	Catalog Number
Black and white nylon. Multiple drive screws.	.230"-.720" (5.8-18.3)	<b>HBL7506C</b> -

## Insulgrip Flanged Inlet

Description	Catalog Number
Nylon casing, polarized, backwired, Multiple drive screws.	- <b>HBL7524C</b>



## Flanged Receptacles

Description	Catalog Numbers
Insulgrip nylon casing, backwired. Multiple drive screws.	<b>HBL7526C</b> -
Metal flange, stainless steel casing, black phenolic, exposed terminals.	<b>HBL7526</b> -

Notes: Only receptacles and plugs are HP rated.  
HP ratings are AC only.  
See pages B-66 and B-67 for accessories.

