

SEARCH OUR PRODUCTS

  
aluminum electrolytic & organic semiconductor

  
film

  
power film

   
tantalum ceramic



## Aluminum Electrolytic Capacitors

### +105°C Standard Radial Lead Aluminum Electrolytic Capacitors

Part Number: 476CKE035M

[General Specifications \(PDF\)](#)

[Special Order Options](#)

[CKH\\_CKE document \(PDF\)](#)



#### Electrical Specifications

**Capacitance:** 47.0  $\mu$ F  
**Tolerance:** -20 %, +20 %  
**Dissipation Factor:** 0.12 at 120 Hz  
**ESR:** 4.233 Ohms at 20° C and 120 Hz  
**Impedance:**  
 --  
 --

**Temperature Range:** -55°C to +105°C  
**WVDC:** 35 volts DC  
**SVDC:** 44. volts DC  
**Leakage Current:**  
 16.0  $\mu$ A after 2 Minutes  
**Ripple Current:**  
 90.0 mA at 120 Hz and 105°C

#### Impedance Ratios:

2.0 at -25°C/20°C  
 3.0 at -40°C/20°C

#### Load Life:

2000 Hours at 105°C with 100% of rated voltage and with 0% of rated ripple current

#### Physical Specifications

**Diameter (D):** 5.0 mm + 0.5 mm  
**Length (L):** 11.0 mm + 1.5 mm  
**Lead Wire Diameter (d):** 0.5 mm + 0.05 mm  
**Lead Spacing:** 2.0 mm +/- 0.5 mm  
**Lead Length:** 15 mm

