

SEARCH OUR PRODUCTS


aluminum electrolytic & organic semiconductor


film


power film


tantalum ceramic

TECH TOOLS

Aluminum Electrolytic Capacitors

+85°C Standard Axial Lead Aluminum Electrolytic Capacitors



Part Number: 107TTA035M

[General Specifications \(PDF\)](#)

[Special Order Options](#)

[TTA document \(PDF\)](#)

Electrical Specifications

Capacitance: 100.0 μ F
Tolerance: -20 %, +20 %
Dissipation Factor: 0.12 at 120 Hz
ESR: 1.989 Ohms at 20° C and 120 Hz
Impedance:
 - and -
 - and -

Temperature Range: -40°C to +85°C
WVDC: 35 volts DC
SVDC: 44. volts DC
Leakage Current:
 105.0 μ A after 1 Minute
Ripple Current:
 210.0 mA at 120 Hz and 85°C

Impedance Ratios:


2.0 -25°C/20°C
 3.0 -40°C/20°C

Load Life:

2000 Hours at 85°C with 100% of rated voltage and with 0% of rated ripple current

Physical Specifications

Diameter (D): 8.0 mm + 0.5 mm
Length (L): 16.0 mm + 1.0 mm
Lead Wire Diameter (d): 0.6 mm + 0.05 mm
Lead Length: 35mm



 **Add To Sample Cart**
 (You can always remove it later)