

Surface Mount Ultrafast Plastic Rectifier



DO-214AC (SMA)

FEATURES

- Low profile package
- Ideal for automated placement
- Glass passivated chip junction
- Ultrafast recovery times for high efficiency
- Low forward voltage, low power losses
- High forward surge capability
- Meets MSL level 1, per J-STD-020, LF maximum peak of 260 °C
- Solder dip 260 °C, 40 s
- Component in accordance to RoHS 2002/95/EC and WEEE 2002/96/EC



RoHS
COMPLIANT

TYPICAL APPLICATIONS

For use in high frequency rectification and freewheeling application in switching mode converters and inverters for consumer, computer, automotive and telecommunication.

MECHANICAL DATA

Case: DO-214AC (SMA)

Epoxy meets UL 94V-0 flammability rating

Terminals: Matte tin plated leads, solderable per J-STD-002 and JESD22-B102

E3 suffix for consumer grade, meets JESD 201 class 1A whisker test, HE3 suffix for high reliability grade (AEC-Q101 qualified), meets JESD 201 class 2 whisker test

Polarity: Color band denotes cathode end

PRIMARY CHARACTERISTICS	
I _{F(AV)}	1.0 A
V _{RRM}	50 V to 200 V
I _{FSM}	30 A
t _{rr}	15 ns
V _F	0.92 V
T _J max.	150 °C

MAXIMUM RATINGS (T _A = 25 °C unless otherwise noted)						
PARAMETER	SYMBOL	ES1A	ES1B	ES1C	ES1D	UNIT
Device marking code		EA	EB	EC	ED	
Maximum repetitive peak reverse voltage	V _{RRM}	50	100	150	200	V
Maximum RMS voltage	V _{RMS}	35	70	105	140	V
Maximum DC blocking voltage	V _{DC}	50	100	150	200	V
Maximum average forward rectified current (Fig. 1)	I _{F(AV)}	1				A
Peak forward surge current 8.3 ms single half sine-wave superimposed on rated load	I _{FSM}	30				A
Operating junction and storage temperature range	T _J , T _{STG}	- 55 to + 150				°C

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise noted)

PARAMETER	TEST CONDITIONS	SYMBOL	VALUE	UNIT
Maximum instantaneous forward voltage $I_F = 1.0 \text{ A}$	$I_F = 0.6 \text{ A}$ (1) $I_F = 1.0 \text{ A}$	V_F	0.865 0.920	V
Maximum DC reverse current at rated DC blocking voltage		I_R	5.0 100	μA
Maximum reverse recovery time	$I_F = 0.5 \text{ A}$, $I_R = 1.0 \text{ A}$, $I_{rr} = 0.25 \text{ A}$	t_{rr}	15	ns
Maximum reverse recovery time	$I_F = 0.6 \text{ A}$, $V_R = 30 \text{ V}$, $dI/dt = 50 \text{ A}/\mu\text{s}$, $I_{rr} = 10\% I_{RM}$	t_{rr}	25 35	ns
Maximum stored charge	$I_F = 0.6 \text{ A}$, $V_R = 30 \text{ V}$, $dI/dt = 50 \text{ A}/\mu\text{s}$, $I_{rr} = 10\% I_{RM}$	Q_{rr}	10 25	nC
Typical junction capacitance	4.0 V, 1 MHz	C_J	10	pF

Note:

(1) Pulse test: 300 μs pulse width, 1 % duty cycle

 THERMAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise noted)

PARAMETER	SYMBOL	ES1A	ES1B	ES1C	ES1D	UNIT
Typical thermal resistance (1)	$R_{\theta JA}$ $R_{\theta JL}$			85	35	$^\circ\text{C}/\text{W}$

Note:

(1) Units mounted on P.C.B. 5.0 x 5.0 mm (0.013 mm thick) land areas

ORDERING INFORMATION (Example)

PREFERRED P/N	UNIT WEIGHT (g)	PREFERRED PACKAGE CODE	BASE QUANTITY	DELIVERY MODE
ES1D-E3/61T	0.064	61T	1800	7" diameter plastic tape and reel
ES1D-E3/5AT	0.064	5AT	7500	13" diameter plastic tape and reel
ES1DHE3/61T (1)	0.064	61T	1800	7" diameter plastic tape and reel
ES1DHE3/5AT (1)	0.064	5AT	7500	13" diameter plastic tape and reel

Note:

(1) Automotive grade AEC-Q101 qualified

RATINGS AND CHARACTERISTICS CURVES

($T_A = 25^\circ\text{C}$ unless otherwise noted)




Figure 1. Maximum Forward Current Derating Curve




Figure 2. Maximum Non-Repetitive Peak Forward Surge Current




Figure 3. Typical Instantaneous Forward Characteristics




Figure 5. Typical Junction Capacitance




Figure 4. Typical Reverse Leakage Characteristics





Figure 6. Typical Thermal Impedance

PACKAGE OUTLINE DIMENSIONS in inches (millimeters)

DO-214AC (SMA)



Mounting Pad Layout

