


Ultrabright LED, \varnothing 5 mm Untinted Non-Diffused



FEATURES

- Untinted non diffused lens
- Utilizing ultrabright AllnGaP (AS)
- High luminous intensity
- High operating temperature:
 T_j (chip junction temperature) up to 125 °C for AllnGaP devices
- Luminous intensity and color categorized for each packing unit
- ESD-withstand voltage:
 up to 2 kV according to JESD22-A114-B
- Lead (Pb)-free component
- Component in accordance to RoHS 2002/95/EC and WEEE 2002/96/EC



DESCRIPTION

The TLC.58.. series is a clear, non diffused 5 mm LED for high end applications where supreme luminous intensity required.

These lamps with clear untinted plastic case utilize the highly developed ultrabright AllnGaP (AS).

The lens and the viewing angle is optimized to achieve best performance of light output and visibility.

APPLICATIONS

- Interior and exterior lighting
- Outdoor LED panels
- Instrumentation and front panel indicators
- Central high mounted stop lights (CHMSL) for motor vehicles
- Replaces incandescent lamps
- Traffic signals
- Light guide design

PARTS TABLE

PART	COLOR, LUMINOUS INTENSITY	ANGLE OF HALF INTENSITY ($\pm \varphi$)	TECHNOLOGY
TLCR5800	Red, $I_V > 7500$ mcd	4°	AllnGaP on GaAs
TLCY5800	Yellow, $I_V > 5750$ mcd	4°	AllnGaP on GaAs

ABSOLUTE MAXIMUM RATINGS¹⁾, TLCR5800, TLCY5800				
Parameter	Test condition	Symbol	Value	Unit
Reverse voltage ²⁾		V_R	5	V
DC Forward current	$T_{amb} \leq 85\text{ °C}$	I_F	50	mA
Surge forward current	$t_p \leq 10\ \mu\text{s}$	I_{FSM}	1	A
Power dissipation		P_V	135	mW
Junction temperature		T_j	125	°C
Operating temperature range		T_{amb}	- 40 to + 100	°C
Storage temperature range		T_{stg}	- 40 to + 100	°C
Soldering temperature	$t \leq 5\ \text{s}, 2\ \text{mm from body}$	T_{sd}	260	°C
Thermal resistance junction/ambient		R_{thJA}	300	K/W

Note:

¹⁾ $T_{amb} = 25\text{ °C}$ unless otherwise specified

²⁾ Driving the LED in reverse direction is suitable for a short term application

OPTICAL AND ELECTRICAL CHARACTERISTICS¹⁾, TLCR5800, RED							
PARAMETER	TEST CONDITION	PART	SYMBOL	MIN	TYP.	MAX	UNIT
Luminous intensity ²⁾	$I_F = 50\ \text{mA}$	TLCR5800	I_V	7500	20 000		mcd
Dominant wavelength	$I_F = 50\ \text{mA}$		λ_d	611	616	622	nm
Peak wavelength	$I_F = 50\ \text{mA}$		λ_p		622		nm
Spectral bandwidth at 50 % $I_{rel\ max}$	$I_F = 50\ \text{mA}$		$\Delta\lambda$		18		nm
Angle of half intensity	$I_F = 50\ \text{mA}$		φ		± 4		deg
Forward voltage	$I_F = 50\ \text{mA}$		V_F		2.1	2.7	V
Reverse voltage	$I_R = 10\ \mu\text{A}$		V_R	5			V
Temperature coefficient of V_F	$I_F = 50\ \text{mA}$		TC_{V_F}		- 3.5		mV/K
Temperature coefficient of λ_d	$I_F = 50\ \text{mA}$		TC_{λ_d}		0.05		nm/K

Note:

¹⁾ $T_{amb} = 25\text{ °C}$ unless otherwise specified

²⁾ in one Packing Unit $I_{Vmax}/I_{Vmin} \leq 2.0$

OPTICAL AND ELECTRICAL CHARACTERISTICS¹⁾, TLCY5800, YELLOW							
Parameter	Test condition	Part	Symbol	Min	Typ.	Max	Unit
Luminous intensity ²⁾	$I_F = 50\ \text{mA}$	TLCY5800	I_V	5750	14 000		mcd
Dominant wavelength	$I_F = 50\ \text{mA}$		λ_d	585	590	597	nm
Peak wavelength	$I_F = 50\ \text{mA}$		λ_p		593		nm
Spectral bandwidth at 50 % $I_{rel\ max}$	$I_F = 50\ \text{mA}$		$\Delta\lambda$		17		nm
Angle of half intensity	$I_F = 50\ \text{mA}$		φ		± 4		deg
Forward voltage	$I_F = 50\ \text{mA}$		V_F		2.1	2.7	V
Reverse voltage	$I_R = 10\ \mu\text{A}$		V_R	5			V
Temperature coefficient of V_F	$I_F = 50\ \text{mA}$		TC_{V_F}		- 3.5		mV/K
Temperature coefficient of λ_d	$I_F = 50\ \text{mA}$		TC_{λ_d}		0.1		nm/K

Note:

¹⁾ $T_{amb} = 25\text{ °C}$ unless otherwise specified

²⁾ in one Packing Unit $I_{Vmax}/I_{Vmin} \leq 2.0$

LUMINOUS INTENSITY CLASSIFICATION		
GROUP STANDARD	LIGHT INTENSITY [MCD]	
	MIN	MAX
FF	1350	2700
GG	1800	3600
HH	2400	4800
II	3200	6400
KK	4300	8600
LL	5750	11 500
MM	7500	15 000
NN	10 000	20 000
PP	13 500	27 000
QQ	18 000	36 000
RR	24 000	48 000
SS	32 000	64 000
TT	43 000	86 000
UU	57 500	115 000

Note:

Luminous intensity is tested at a current pulse duration of 25 ms and an accuracy of $\pm 11\%$.

The above type numbers represent the order groups which include only a few brightness groups. Only one group will be shipped on each bag (there will be no mixing of two groups on each bag).

In order to ensure availability, single brightness groups will not be orderable.

In a similar manner for colors where wavelength groups are measured and binned, single wavelength groups will be shipped in any one bag.

In order to ensure availability, single wavelength groups will not be orderable.

TYPICAL CHARACTERISTICS

$T_{amb} = 25\text{ }^\circ\text{C}$, unless otherwise specified




Figure 1. Forward Current vs. Ambient Temperature

COLOR CLASSIFICATION				
GROUP	DOM. WAVELENGTH (NM)			
	YELLOW		RED	
	MIN.	MAX.	MIN.	MAX.
0	585	588		
1	587	591	611	618
2	589	594	614	622
3	592	597		

Note:

Wavelengths are tested at a current pulse duration of 25 ms and an accuracy of $\pm 1\text{ nm}$.




Figure 2. Relative Intensity vs. Wavelength




Figure 3. Relative Intensity vs. Wavelength




Figure 5. Relative Luminous Flux vs. Forward Current




Figure 4. Forward Current vs. Forward Voltage





Figure 6. Relative Luminous Flux vs. Forward Current

PACKAGE DIMENSIONS IN MM



Drawing-No: 6544-5258.04-4
Issue: 6; 04.07.03

9612121