



BU-00000- \*  
Part # color

\* 0 - Black 5 - Green  
2 - Red 6 - Blue  
4 - Yellow 9 - White

**CLIPS & INSULATORS**



- BU-34 Steel Micro-Alligator 5 Amp**  
**BU-34C Solid Copper Micro-Alligator 5 Amp**
- Smooth jawed clip has a microscopic tip
  - Nose width is 0.0625" (1.6mm)
  - Solder or crimp connection
  - 7/32" (5.6mm) max. jaw opening

**BU-36 Insulator for BU-34/34C**

- Skin-tight flexible vinyl
- Available in black, red, yellow, green, blue and white



- BU-30 Steel Miniature-Alligator 5 Amp**  
**BU-30C Solid Copper Miniature-Alligator 5 Amp**
- Full meshing teeth
  - Jaw opens 3/16" (4.8mm) max.
  - Solder or crimp connection
  - 7/32" (5.6mm) jaw opening
  - Federal spec.: Type TCM-1-W-C-440B(BU-30C)

**BU-32 Insulator for BU-30/30C**

- Skin-tight flexible vinyl
- Available in black, red, yellow, green, blue and white



[Contents](#)|[Next](#)

[Home](#)|[Insulated BNCs](#)|[Test Leads](#)|[Insulated Test Accessories](#)  
[Accessories & Probes](#)|[Kits](#)|[Cross Reference](#)

©2000 Mueller Electric Company. All rights reserved.  
Problems with the site should be reported to the [webmaster](#).  
This site created by [WebEcentric](#).