lumbergautomation

A BELDEN BRAND

## **RKMV / RSMV**

a

3 and 4 Pole


Pico (M8) single ended cordset, female and male, straight, 3and 4-pole with self locking thread, joint and molded 22 and 24 AWG, orange PVC cable, IEC color code, IP67 and NEMA 6P rated.






**RKMWV / RSMWV** 







Ø9,8

\*a O-Ring O-ring









1 = brown

3 = blue

4 = black





1 = brown 2 = white 3 = blue4 = black

Ø9.8

DSM8031809001C

Connectors and Components for Industrial Automation / Pico (M8) Single Ended Cordsets Lumberg Automation / 1540 Orchard Drive, Chambersburg, PA 17201 / Tel. (717) 217-2279 / Fax (717) 217-2279

## 3 and 4 Pole

Pico (M8) single ended cordset, female and male, right angle, 3and 4-pole with self locking thread, joint and mold 22 and 24 AWG, orange PVC cable, IEC Color Code, IP67 and NEMA 6P rated. **IEC Color Code** 

UL Type: AWM 2464

Gauge: 22 and 24

PVC



F)

A BELDEN BRAND

3-4 poles: 4 A

<b>Technical Data</b> Degree of protection Operating temperature range	IP67/ IP69K -25°C (-13°F) / +80°C (+176°I			
Mechanical Molded body Insert Contact	TPU, translucent TPU, self-extinguishing Brass, pre-nickeled and 0.8 microns gold-plated			
Coupling nut	Brass, nickel-plated			
Electrical Contact resistance	≤5mΩ			
Voltage rating	3 poles: 63 V 4 poles: 36 V			

**Cable Specifications** Cable Outer Conductor Color Outside Number Jacket Size Diameter PVC 22 AWG 06 Orange .197" (5.0 mm) 07 PVC 24 AWG Orange .197" (5.0 mm)

Mating Receptacles							
Part Number	Receptacle	Part Number	Receptacle				
RKMV 3-06/M	RSMF 3/0.5M	RSMV 3-06/M	RKMF 3/0.5 M				
RKMWV 3-06/M	RSMHL 3/S 5,5	RSMWV 3-06/M	RKMHL 3/S 5,5				
RKMV 4-07/M	RSMF 4/0.5M	RSMV 4-07/M	RKMF 4/0.5 M				
RKMWV 4-07/M	RSMHL 4/S 5,5	RSMWV 4-07/M	RKMHL 4/S 5,5				

Part Number				Poles	
Female Straight	Male Straight	Female Right Angle	Male Right Angle		
RKMV 3-06/M	RSMV 3-06/M	RKMWV 3-06/M	RSMWV 3-06/M	3	
RKMV 4-07/M	RSMV 4-07/M	RKMWV 4-07/M	RSMWV 4-07/M	4	

Current rating

## Standard cable lengths: 2 M / 5 M / 10 M Other cable lengths or cable specifications on request.

Connectors and Components for Industrial Automation - www.lumberg-automationusa.com Lumberg Automation / 1540 Orchard Drive, Chambersburg, PA 17201 / Tel. (717) 217-2279 / Fax (717) 217-2279