

HT-7715DNV

speco technologies®

Color Day/Night Weatherproof Camera



HT-7715DNV

Features

- 1/3" SONY ExView* CCD sensor - 470 lines of resolution • Split Glass Technology to avoid IR reflections
- Auto iris DC Vari-Focal Lens (4mm-9mm)
- LUX level dip switch adjusts day/night settings to your requirements
- Dual voltage operation • Built-in 11 IR LEDs (60' Range**) & CDS sensor for day/night performance
- Controls for BLC, ELC, F/L and L/L • Video Test Connector for easy installation
- Built-in heater extends operating range and avoids condensation • Weatherproof operation
- Excellent low light level performance - 0.03 Lux in existing light, 0.0 Lux with IR LEDs

Specifications

Image Sensor	1/3" Sony ExView* CCD
Resolution	470 lines
Minimum Illumination003 lux (IR off) 0.00 lux (IR on)
Lens	DC Auto iris, 4mm-9mm (Varifocal)
CDS Sensor	Photoconductive cells - adjustable
Electronic Shutter	1/60 - 1/100,000 seconds
Video Output	1.0 Vp-p into 75 ohms composite
TV System	NTSC
Scanning System	2:1 Interlace
Sync System	Line locked/ adjustable V-phase Line lock/internal on-off
S/N Ratio	More than 60 dB
Gamma Characteristic	0.45
Power Supply	24 Volts AC, 12 Volts DC- dual voltage
Power Consumption	600mA
Operating Temperature	-20°F to 122°F - RH 95%
Dimensions	2.4"W x 2.25"H x 7"L
Weight	1 lb.

*ExView is a trademark of the Sony Corporation
 **Depending on scene reflection

Package Includes:

HT-7715DNV Camera	Instructions	Video Test Cable
Mounting Hardware	Warranty card	

Specifications subject to change