

SEARCH OUR PRODUCTS

  
aluminum electrolytic & organic semiconductor

  
film

  
power film

  
tantalum ceramic

TECH TOOLS



## Aluminum Electrolytic Capacitors

**+105°C High Frequency Low Impedance Radial Lead Aluminum Electrolytic Capacitor**



**Part Number: 157KXM035M**

[General Specifications \(PDF\)](#)

[Special Order Options](#)

[KXM document \(PDF\)](#)

### Electrical Specifications

**Capacitance:** 150.0  $\mu$ F  
**Tolerance:** -20 %, +20 %  
**Dissipation Factor:** 0.12 at 120 Hz  
**ESR:** 1.326 Ohms at 20° C and 120 Hz  
**Impedance:**  
 0.072 Ohms at 20°C 100 kHz  
 0.22 Ohms at -10°C 100 kHz

**Temperature Range:** -40°C to +105°C

**WVDC:** 35 volts DC

**SVDC:** 44. volts DC

**Leakage Current:**  
52.5  $\mu$ A after 2 Minutes

**Ripple Current:**  
760.0 mA at 100 kHz and 105°C

**Impedance Ratios:**

2.0 at -25°C/20°C

3.0 at -40°C/20°C

**Load Life:**

3000 Hours at 105°C with 100% of rated voltage and with 100% of rated ripple current

### Physical Specifications

**Diameter (D):** 8.0 mm + 0.5 mm

**Length (L):** 11.5 mm + 2.0 mm

**Lead Wire Diameter (d):** 0.6 mm + 0.05 mm

**Lead Spacing:** 3.5 mm +/- 0.5 mm

**Lead Length:** 15 mm

