


## AC-Capacitors, Suppression Capacitors Class Y2 (X1) AC 305V (MKT)



**FEATURES:**

Product is completely lead (Pb)-free  
Product is RoHS compliant

**REFERENCE STANDARDS:**

EN/IEC 60068; IEC 60384-14/2 1993/07  
UL 1414; CSA C22 2 No. 1-M 1994

**DIELECTRIC:** Polyester film

**ELECTRODES:** Metal evaporated

**RATED VOLTAGE:** AC305V; 50/60Hz

**PERMISSIBLE DC VOLTAGE:** DC1000V

**CAPACITANCE RANGE:** E12 series 1000pFY2 -0.1µFY2(X1)  
preferred values acc. to E6

**CAPACITANCE TOLERANCE:**

Standard ± 20%; on request ± 10% and ± 5%

**TERMINALS:**

Radial tinned copper wire

**COATING:** Plastic case, epoxy resin sealed,  
flame retardant; UL 94V-0

**CLIMATIC TESTING CLASS ACC. TO**

**EN/IEC 60068-1:** 40/100/56

**TEST VOLTAGE:**

(Electrode/electrode): DC 5000V for 1 sec. at 25°C;  
Between interconnected terminations and case (foil method);  
AC 2500V for 2 sec. at 25°C

**DISSIPATION FACTOR TAN δ:** < 1% measured at 1kHz

**INSULATION RESISTANCE:**

30 GΩ average value  
15 GΩ average value

**FURTHER TECHNICAL DATA:**

See page 71 (Document Number 26525)



**RoHS  
COMPLIANT**



LEAD LENGTH (X) (mm)		ORDERING CODE** (see page 49 - Document No. 26511)					
Code Pos.11		1-4	5-7	8	9	10	11-13
4 <sup>-1</sup>	B	1710	...	.	3	.	B.0
6 <sup>-1</sup>	C	1710	...	.	3	.	C.0
15 <sup>-1</sup>	D	1710	...	.	3	.	D.0
30 <sup>+5</sup>	L	1710	...	.	3	.	L.0

pcm (mm)	Pitch Code Pos. 10	Terminal Ød (mm)
10	D	0.6
> 10	F, I or K	0.8

MAXIMUM PULSE RISE TIME: (du/dt) in V/µs			
RATED VOLTAGE	PITCH (mm)		
	10.0/15.0	22.5	27.5
AC 305V	200	150	100

CAPACITANCE Code Pos 5-7 (as class Y2 and X1)	TOLERANCE Code Pos 8 J = ± 5% K = ± 10% M = ± 20%	PITCH Code Pos. 10 (mm)	BOX NO	DIMENSIONS W x H x L (mm) <sup>+0.2 / -0.4mm</sup>	WEIGHT (Lead Length 6 <sup>-1</sup> mm) (g)	QUANTITY PACKAGE (Lead Length ≤ 6 <sup>-1</sup> mm) (pcs)*	ORDERING CODE**					Lead Length Design Design
							TYPE	C-Value	Tolerance	Voltage	Pitch	
							1-4	5-7	8	9	10	11-13
1000 pF	M	10.0	D	32	3.8 x 8.8 x 12.8	0.6	1710	210	M	3	D	.B0
1200 pF	M	10.0	D	32	3.8 x 8.8 x 12.8	0.6	1710	212	M	3	D	.B0
1500 pF	M	10.0	D	32	3.8 x 8.8 x 12.8	0.6	1710	215	M	3	D	.B0
1800 pF	M	10.0	D	32	3.8 x 8.8 x 12.8	0.6	1710	218	M	3	D	.B0
2200 pF	M	10.0	D	02	4.3 x 9.3 x 12.8	0.8	1710	222	M	3	D	.B0
2700 pF	M	10.0	D	03	5.3 x 10.3 x 12.8	1.0	1710	227	M	3	D	.B0
3300 pF	M	10.0	D	03	5.3 x 10.3 x 12.8	1.0	1710	233	M	3	D	.B0
3900 pF	M	10.0	D	03	5.3 x 10.3 x 12.8	1.0	1710	239	M	3	D	.B0
4700 pF	M	10.0	D	03	5.3 x 10.3 x 12.8	1.0	1710	247	M	3	D	.B0
5600 pF	M	10.0	D	04	6.3 x 11.3 x 12.8	1.3	1710	256	M	3	D	.B0
6800 pF	M	10.0	D	04	6.3 x 11.3 x 12.8	1.3	1710	268	M	3	D	.B0
8200 pF	M	10.0	D	04	6.3 x 11.3 x 12.8	1.3	1710	282	M	3	D	.B0
0.010 µF	M	10.0	D	04	6.3 x 12.3 x 12.8	1.3	1710	310	M	3	D	.B0

\* Further information about packaging quantities with different lead length and/or taped versions.

See page 16 (Document No 27608 Packaging Quantities). Use Box No. as reference

\*\* These capacitors can be delivered on continuous tape and reel see page 14/15 (Document Number 27622)

Ordering example: 1710-210 M 2 D CB0

B0 = Bulk Pack T0 = Tray/Pallet



CAPACITANCE Code Pos 5-7 (as class Y2 and X1)	TOLERANCE Code Pos 8 J = ± 5% K = ± 10% M = ± 20%	PITCH		BOX NO	DIMENSIONS W x H x L  (mm) <sup>+0.2 / -0.4mm</sup>	WEIGHT  (Lead Length 6 <sup>+</sup> mm)  (g)	QUANTITY  PACKAGE (Lead Length ≤ 6 <sup>+</sup> mm)  (pcs)*	ORDERING CODE**					
		(mm)	Code Pos. 10					TYPE	C-Value	Tolerance	Voltage	Pitch	Lead Length Design Code
								1-4	5-7	8	9	10	11-13
1000 pF	M	15	F	05	5.3 x 10.3 x 17.8	1.4	750	1710	210	M	3	F	. B0
1200 pF	M	15	F	05	5.3 x 10.3 x 17.8	1.4	750	1710	212	M	3	F	. B0
1500 pF	M	15	F	05	5.3 x 10.3 x 17.8	1.4	750	1710	215	M	3	F	. B0
1800 pF	M	15	F	05	5.3 x 10.3 x 17.8	1.4	750	1710	218	M	3	F	. B0
2200 pF	M	15	F	05	5.3 x 10.3 x 17.8	1.4	750	1710	222	M	3	F	. B0
2700 pF	M	15	F	05	5.3 x 10.3 x 17.8	1.4	750	1710	227	M	3	F	. B0
3300 pF	M	15	F	05	5.3 x 10.3 x 17.8	1.4	750	1710	233	M	3	F	. B0
3900 pF	M	15	F	05	5.3 x 10.3 x 17.8	1.4	750	1710	239	M	3	F	. B0
4700 pF	M	15	F	05	5.3 x 10.3 x 17.8	1.4	750	1710	247	M	3	F	. B0
5600 pF	M	15	F	05	5.3 x 10.3 x 17.8	1.4	750	1710	256	M	3	F	. B0
6800 pF	M	15	F	05	5.3 x 10.3 x 17.8	1.4	750	1710	268	M	3	F	. B0
8200 pF	M	15	F	06	6.3 x 12.3 x 17.8	2.0	500	1710	282	M	3	F	. B0
0.01 μF	M	15	F	06	6.3 x 12.3 x 17.8	2.0	500	1710	310	M	3	F	. B0
0.012 μF	M	15	F	07	7.3 x 13.3 x 17.8	2.4	450	1710	312	M	3	F	. B0
0.015 μF	M	15	F	07	7.3 x 13.3 x 17.8	2.4	450	1710	315	M	3	F	. B0
0.018 μF	M	15	F	28	8.3 x 17.3 x 17.8	3.4	300	1710	318	M	3	F	. B0
0.022 μF	M	15	F	28	8.3 x 17.3 x 17.8	3.4	300	1710	322	M	3	F	. B0
0.027 μF	M	22.5	I	09	6.3 x 14.3 x 26.3	3.5	260	1710	327	M	3	I	. . 0
0.033 μF	M	22.5	I	09	6.3 x 14.3 x 26.3	3.5	260	1710	333	M	3	I	. . 0
0.039 μF	M	22.5	I	11	7.3 x 15.3 x 26.3	3.9	235	1710	339	M	3	I	. . 0
0.047 μF	M	22.5	I	12	8.3 x 16.3 x 26.3	4.8	200	1710	347	M	3	I	. . 0
0.056 μF	M	22.5	I	13	10.3 x 18.3 x 26.3	6.6	170	1710	356	M	3	I	. . 0
0.068 μF	M	22.5	I	13	10.3 x 18.3 x 26.3	6.6	170	1710	368	M	3	I	. . 0
0.082 μF	M	27.5	K	14	11.0 x 20.3 x 31.3	9.4	125	1710	382	M	3	K	. . 0
0.1 μF	M	27.5	K	14	11.0 x 20.3 x 31.3	9.4	125	1710	410	M	3	K	. . 0

Preferred values in bold print.

\* Further information about packaging quantities with different leadlength and/or taped versions.



See page 16 (Document No 27608 Packing Quantities). Use Box No as reference

\*\* These capacitors can be delivered on continuous tape and reel see page 14/15 (Document Number 27622)

The ordering code is then: F1710 - . . . M 3 . 0R0 at H = 16.5mm, F1710 - . . . M 3 . 0W0 at H = 18.5mm.

APPROVALS

COUNTRY	SPECIFICATION	ELECTRICAL VALUES	APPROVAL REFERENCE	APPROVAL MARK
U.S.A (for AC 250V)	UL 1283 UL 1414	1000pFY - 0.1μFY 1000pFY - 0.1μFY	E 76297 E 100682	
Canada (for AC 250V)	C 22.2 No. 1-M 1994	1000pFY - 0.1μFY	LR 64546-7	
<b>CB TEST-CERTIFICATE (for AC 305V)</b>		1000pF - 0.1μFY2 (X1)	DE 1-10088	
Germany (for AC 305V)	EN 132 400, 1999-06 IEC 60384-14, 2nd edition, 1995-06	1000pF - 0.1μFY2 (X1)	136954L	



Impedance (Z) as a function of frequency (f) at T<sub>a</sub> = 20°C (average). Measurement with lead length 6mm.



## Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.