



Front size	18 mm dia. 18 x 18 mm 18 x 24 mm
Front protection	IP 65
Mounting hole size	16 mm dia.
Switching System	Low level switching element Snap-action switching element
Switch rating	250 VAC, 5 A 42 VAC, 100 mA
Illumination	Filament lamp LED

250VAC 16mm **IP65 5A**

Series 51

Product Profile

are also available.


IP65 Protection

• Switch Rating, 5A, 250VAC

lamps or single chip LED's

• QC versions also available

are available in different colors



indicators, illuminated selector

Choose one component from each of the colored sections to assemble a complete switch. For other options or further information please contact EAO Switch directly.

O-Indicator Illuminated pushbutton The Series 51 is a high quality switch range that includes pushbuttons, switches and keylock switches. It is possible to choose up to 4NO/4NC snap-action switching elements per switch. Low level switching elements **Technical drawings see pages 56-57** Indicator bodies, raised in round, square and Illuminated pushbutton, snap-action, raised, rectangular, black plastic, 16mm mounting, rectangular, black plastic, 16mm mounting, solder terminals solder terminals, gold over silver contacts Raised Mounting into 16mm cut out Part No. Size Part No. Contact type Image Action Size 51-040.005 18 x 24mm 1N0/1NC Illumination using midget-grooved T-1¹/₃ 51-121.025 Momentary 18 x 24mm 1 2 51-050.005 51-122.025 2N0/2NC 18 x 24mm 18 x 18mm Momentary 3 51-030.005 18mm Ø 51-261.025 Maintained 1NO/1NC 18 x 24mm All standard lenses are transparent 51-262.025 Maintained 2N0/2NC 18 x 24mm with translucent white diffusers, and For keylock switches 2 key systems and 145 different key codes are available

For complete switch also order 🖉 🗛

For complete switch also order $\ddot{\mathbf{Q}}$

Illuminated pushbutton



Illuminated pushbutton, snap-action, raised, square, black plastic, 16mm mounting, solder terminals, gold over silver contacts



Illuminated pushbutton, snap-action, raised, round, black plastic, 16mm mounting, solder terminals, gold over silver contacts



Keylock switch, 2 position raised, snap-action, round, black plastic, 18mm Ø, solder

Solder terminals, gold over silver contacts							terminals, gold over silver contacts				
Part No.	Action	Contact type	Size	Part No.	Action	Contact type	Size	Drawing	Part No.	Contact type	Key rem.
51-151.025	Momentary	1N0/1NC	18 x 18mm	51-131.025	Momentary	1N0/1NC	18mm Ø	1	51-135.025D	1N0/1NC	A+C
51-152.025	Momentary	2N0/2NC	18 x 18mm	51-132.025	Momentary	2N0/2NC	18mm Ø	1	51-136.025D	2N0/2NC	A+C
51-281.025	Maintained	1N0/1NC	18 x 18mm	51-271.025	Maintained	1N0/1N0	18mm Ø	1	51-235.025D	1N0/1NC	А
51-282.025	Maintained	2N0/2NC	18 x 18mm	51-272.025	Maintained	2N0/2NC	18mm Ø	1	51-335.025D	1N0/1NC	С
								2	51-141.025D	1N0/1NC	А


For complete switch also order 🍟 🛕

For complete switch also order 🍟 🛕

51 Indicator Raised


51 Pushbutton

Raised, Round, Square, Rectangular




51 Keylock

Raised, 2-Position, Round, Square, Rectangular



52 Selector

Raised, 2-Position, Round



52 Selector

Raised, 3-Position, Round

