

Model #: INTERNETOFFICE300

Internet Office UPS System- All-in-one SOHO solution



Highlights

300VA ultra-compact UPS
Maintains 120V nominal output during blackouts
Basic power-only UPS with status LEDs
Input: NEMA 5-15P (120V 15A) / Output: 6 NEMA 5-15R (120V)
2 year product warranty

Description

Tripp Lite's INTERNETOFFICE300 UPS System provides complete power protection for your entire computer set-up. 300 VA power capacity maintains your Internet connection allowing you to work online through short blackouts or safely shut down during longer ones. Unique design features 6 outlets (3 UPS & surge + 3 surge-only outlets) and diagnostic LEDs. Built-in RJ45 jacks prevent surges from damaging your modem/fax/10BT equipment. A 6-ft. telephone cord is also included.

Applications

Personal computers with modems, network workstations, home-office workstations, point-of-sale terminals and more.

Package Includes

INTERNETOFFICE300 UPS System

6-ft. telephone cord

Instruction manual with warranty information

Features

300 VA output power rating (150 watts)

Up to 11 minutes backup time (single PC; 15-in monitor)

Battery run time: 10 minutes half load/4 minutes full load

6 protected outlets (3 UPS & surge + 3 surge-only outlets); 6-ft. cord

Built-in RJ45 jacks prevent surges from damaging your modem/fax/10BT equipment; 6-ft. telephone cord included

Complete surge protection and EMI/RFI noise filtering

5 diagnostic LEDs indicate AC present, line fault, on battery, overload and battery low/replace

Specifications

SYSTEM OVERVIEW	
Voltage compatibility	120V AC
Frequency compatibility	50/60Hz

OUTPUT	
Output VA	300
Output watts	150
Output nominal voltage	120V AC
Output voltage regulation	LINE MODE: Passes sine wave line voltage from 100-141V to connected equipment unchanged BATTERY MODE: PWM sine wave output 120V +/-5%
Output frequency regulation	LINE MODE: Passes line frequency of 60Hz +/-10% BATTERY MODE: Inverter output regulated to 60Hz +/-0.5Hz
Outlet quantity / type	6 NEMA 5-15R
INPUT	
Input connection type	NEMA 5-15P
Input cord length	6 ft., 14 gauge
Recommended Electrical Service	15A 120V
BATTERY	
Full load runtime	4 minutes (300VA)
Half load runtime	10 minutes (150VA)
DC system voltage	12 VDC
Typical battery lifespan	3-6 years, depending on usage
Battery recharge rate	2-4 hours to 90%
LEDS ALARMS & SWITCHES	
Front panel LEDs	5 LEDs indicate complete UPS operational status
Switches	Power off / on switch
SURGE / NOISE SUPPRESSI	ON
AC surge suppression	380 joules
AC suppression response time	Instantaneous
Dataline suppression	Tel/DSL/Ethernet
EMI / RFI AC noise suppression	Yes
PHYSICAL	
Shipping weight (lbs)	5.4
Shipping weight (kg)	2.5
Shipping Dimensions (HWD/in)	4.5 x 13 x 8.25
Shipping Dimensions (HWD/cm)	11.4 x 33 x 20.9
Unit weight (lbs)	4
Unit weight (kg)	1.8
Unit Dimensions (HWD/in)	2.6 x 11 x 4.5
Unit Dimensions (HWD/cm)	6.6 x 27.9 x 11.4
Material of construction	Plastic
Form factors supported	Ultra-compact
ENVIRONMENTAL	· · · · · · · · · · · · · · · · · · ·
Operating Temperature	+32 to +104 degrees Fahrenheit

Storage Temperature	+5 to +122 degrees Fahrenheit			
Relative Humidity	0 to 95%, non-condensing			
LINE / BATTERY TRANSFER				
Transfer time from line power to battery mode	2-4 milliseconds			
Low voltage transfer to battery power	approx. 99VAC			
High voltage transfer to battery power	approx. 141VAC			
SPECIAL FEATURES				
Appearance	Attractive black ultra-compact housing			
CERTIFICATIONS				
Certifications	Tested to UL1778 (USA), CSA (Canada), Class B (emissions), NOM (Mexico), FCC Part 68 / Industry Canada (telecommunications)			
WARRANTY				
Product warranty	2 years			
Optional coverage	Optional 3 and 5 year extented warranties available			

Related Items

Extended Warranties			
WEXT3-INTERNET	3-Year Extended Warranty - For Internet Office Models	Qty: [optional]	
WEXT5-INTERNET	5-Year Extended Warranty - For Internet Office Models	Qty: [optional]	

©2009 Tripp Lite. All Rights Reserved.