

MWLT100 Series

100W single output Medical AC/DC Power Supplies

The MWLT100 Series of single output convection cooled products are one of the smallest and most efficient 100-watt power supply packages available in the industry today typically 1/3rd the size and 20% more efficient than leading competitors. Packing nearly 12 watts per cubic inch the MWLT100 Series features Universal AC inputs from 90v to 264v, measures a mere 2 inches x 4 inches x 1.07 inches, and has a rated efficiency of greater than 86%. It is configured in all popular single output voltages and its flexible design allows for simple modification to alternate voltages as required.

The MWLT1000 Series meets all medical EMC and safety specifications, and has a reliability rating of over 200,000 hours mean time between failure. The MWLT100 Series is produced with the traditional EOS red color heat sink signifying its medical market application.

Medical product applications for the MWLT100 family include: medical, dental and lab equipment and systems such as endoscopes, instruments, pumps, drips, blood and fluid analyzers, video systems, defibrillators, sleep apnea, nurse call stations and many other uses.



Features :

- > 100 W air cooled rating.
- > Small 2x4x1 inch form factor.
- > High efficiency > 86%.
- > Single outputs.
- > Low conducted and radiated noise.
- > Medically Approved
- > Class 1 Product
- > Active PFC

Model Number	Output	Voltage / Current *	Voltage Set Point	Min. Load
MWLT100-1001	V1	12V@8.3A	12V	0. 1A
MWLT100-1002	V1	15V@6.67A	15V	0. 1A
MWLT100-1003	V1	24V@4.17A	24V	0. 1A
MWLT100-1004	V1	48V@2.08A	48V	0. 1A
VLT60CK	Metal cover kit accessory			

INPUT SPECIFICATION		
AC Input	Universal	90 to 264VAC
DC Input		120 to 390VDC (Reduce to half load at 120VDC Input)
Efficiency	All Models	≥86%
Input Frequency		47-63 Hz
Input Current	Full Load at High line	1.5Arms , max
Inrush Current	High Line , cold start	60A, max

OUTPUT SPECIFICATION		
Output Power		100W max
Leakage Current	Typical Values	170 to 220uA
Hold-Up Time	115V/230V	6ms./15ms
Voltage Set Point Accuracy	V1	±2%
Line Regulation	Low line to high line	0.3%
Load Regulation	Min to Max load	0.5%
Transient Response	50% to full load Voltage Deviation Recovery Time	10%, max <5 ms
OVP	Self Protecting	Auto Recovery
Overload Protection	Primary limited	110% to 130%
Short Circuit Protection	Auto recovery <6s	Short Term
Ripple and Noise	All Output Volatges	<1%
Output Rise Time	All outputs	<100ms

* Maximum current per output channel. Do not exceed total output power rating

All Red Rocket, Inc. EOS power supplies have UL, CSA and Nemko safety compliance and medical versions meet UL60601-1 standards. All our products are RoHS compliant. Visit us at www.redrocketpower.com and contact us at: sales@redrocketpower.com or by calling +1 805-409-0909 today.

© 2008, Red Rocket, Inc. EOS brand power supplies and patents are owned exclusively by Red Rocket, Inc. All Rights Reserved.

REV 04-09-08




MWLT100 Series

100W Medical AC/DC Power Supplies



EMC AND SAFETY SPECIFICATIONS	
CE Mark	Complies with the LVD
EMC	EN5022-B, CISPR22-B, FCC Part 15 Class B, EN50082-1
Agency Approval	VDE, UL, c-UL
Safety Standard	EN60601-1-2
Safety file number	UL: EI73812
Isolation	4KVAC Input to Output 1500VAC Input to GND
Insulation Resistance	7mOhms Input to Output

ENVIRONMENTAL SPECIFICATION		
Operating Temperature	Convection 50LFM Airflow Refer to de-rating	-20 to 30° C -20 to 50° C To 70° C
Storage Temperature		-40 to 85° CC
Cooling		Convection 50LFM Airflow
Relative humidity	Non condensing	95%, max
MTBF	MIL - HDBK-217F	> 200,000 hrs
Altitude		Operating: 10,000ft Non-Operating: 40,000ft
Vibration	Operating & Non Operating	5-9Hz, 2G PK, 0.5 oct./min, 2 cycles; 9-500Hz 0.5 oct./min, 2 cycles.
Transients		EN61000-4-2, 4-3, 4-4, 4-5, 4-6, 4-11 Level 3



All Red Rocket, Inc. EOS power supplies have UL, CSA and Nemko safety compliance and medical versions meet UL60601-1 standards. All our products are RoHS compliant. Visit us at www.redrocketpower.com and contact us at: sales@redrocketpower.com or by calling +1 805-409-0909 today.
© 2008, Red Rocket, Inc. EOS brand power supplies and patents are owned exclusively by Red Rocket, Inc. All Rights Reserved.
REV 04-09-08



MWLT100 Series

100W Medical AC/DC Power Supplies




MECHANICAL SPECIFICATION	
AC Input Connector J1	Molex 3 position, 0.156 center Mating Connector: Molex 09-50-3031 Pins: 08-50-0106
Ground Connector	Molex 19705-4301 PCB Quick Disconnect Mating: Molex AA-1140
DC Output connector J2	Molex 4 position, 0.156 center Mating Connector: Molex 09-50-8041 Pins: 08-52-0072
Size	4"x2"x1.07"
Weight	5oz (150g)

OUTPUT CONNECTOR J2	
	Single Output
Pin1	RTN
Pin2	RTN
Pin3	V1
Pin4	V1

INPUT CONNECTOR J1	
Pin 1	AC Neutral
Pin2	AC Line

INPUT SPADE CONNECTOR	
GND	AC Ground



All Red Rocket, Inc. EOS power supplies have UL, CSA and Nemko safety compliance and medical versions meet UL60601-1 standards. All our products are RoHs compliant. Visit us at www.redrocketpower.com and contact us at: sales@redrocketpower.com or by calling +1 805-409-0909 today.
© 2008, Red Rocket, Inc. EOS brand power supplies and patents are owned exclusively by Red Rocket, Inc. All Rights Reserved.

REV 04-09-08

red rocket
inc.