

## CircuitWorks® Flux Remover Pens

### TYPICAL PRODUCT DATA AND PHYSICAL PROPERTIES

#### PRODUCT DESCRIPTION


CircuitWorks® Flux Remover Pens are designed specifically to remove each type of flux. The Rosin Flux Remover Pen quickly cleans type R, RMA, and RA flux residues. The No Clean Flux Remover Pen precisely removes both organic and synthetic low solid no clean fluxes.

- A pen for removing rosin flux residues
- A pen for spot removal of no clean fluxes
- Penetrates hard to reach areas
- Marker pen dispenser provides controlled and exact application
- Removes ionic and non-ionic residues
- Excellent material compatibility
- Fast drying

#### TYPICAL APPLICATIONS

CircuitWorks® Flux Remover Pens remove flux residues and clean precise areas on:

- Printed Circuit Boards
- Chip Carriers
- Heat Sinks
- Surface Mount Device Pads
- Switches
- Sockets

| <b>Rosin Flux Remover Pen</b>         |   |
|---------------------------------------|---|
| Flash Point (TCC)                     | 70 °F (21 °C)   |
| Vapor Density (air=1)                 | > 1   |
| Surface Tension                       | 21.3 dyne/cm  |
| Appearance                            | Clear Liquid  |
| Odor                                  | Alcohol   |
| <b>No Clean Flux Remover Pen</b>      |   |
| Flash Point (TCC)                     | 102 °F (39 °C)  |
| Vapor Density (air=1)                 | > 1   |
| Surface Tension                       | 17.7 dyne/cm  |
| Appearance                            | Clear Liquid  |
| Odor                                  | Characteristic  |
| <b>Water Soluble Flux Remover Pen</b> |   |
| Flash Point (TCC)                     | 70 °F (21 °C)   |
| Vapor Density (air=1)                 | > 1   |
| Surface Tension                       | 21.1 dyne/cm  |
| Appearance                            | Clear Liquid  |
| Odor                                  | Alcohol   |
| <b>Shelflife</b>                      | 5 years   |
| <b>RoHS/WEEE Status</b>               |  |

## **COMPATIBILITY**

CircuitWorks<sup>®</sup> Flux Remover Pens are generally compatible with most materials used in the electronics industry. As with any cleaning agent, material compatibility should be determined on a non-critical area prior to use.

## **USAGE INSTRUCTIONS**

For industrial use only.

Read MSDS carefully prior to use.

Hold pen vertically and briefly depress tip to start liquid flow. Rub pen tip on surface to be cleaned. Wipe tip on a ControlWipe<sup>™</sup> dry wipe to remove buildup.

**CAUTION:** Product is Flammable - Do not use near sources of ignition and energized equipment.

## **AVAILABILITY**

CW9100 9 gm (0.32 oz) No Clean Flux Remover Pen

CW9200 8 gm (0.28 oz) Rosin Flux Remover Pen

**NOTE:** This information is believed to be accurate. It is intended for professional end users having the skills to evaluate and use the data properly.

CHEMTRONICS<sup>®</sup> does not guarantee the accuracy of the data and assumes no liability in connection with damages incurred while using it.

**SECTION 1: CHEMICAL PRODUCT AND COMPANY INFORMATION**

Product Information: 800-TECH-401

**Product Identification****CIRCUITWORKS ROSIN FLUX REMOVER PEN**

Product Code: CW9200

**SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS**

| Product Ingredient Information | CAS#     | Wt. % Range |
|--------------------------------|----------|-------------|
| Isopropanol                    | 67-63-0  | 93.0-99.0   |
| Hexamethyldisiloxane           | 107-46-0 | 0.1-2.0     |
| n-Propyl acetate               | 109-60-4 | 1.0-5.0     |

**SECTION 3: HAZARD IDENTIFICATION**

**Emergency Overview:** Clear, colorless liquid with strong alcohol odor. This product is flammable. Liquid will irritate eyes and skin under repeated or prolonged exposure. Breathing high concentrations of product vapor may produce drowsiness and a headache.

**Potential Health Effects:**

**Eyes:** Liquid, aerosols and vapors of this product are irritating and can cause pain, tearing, reddening and swelling accompanied by a stinging sensation.

**Skin:** Contact causes skin irritation.

**Ingestion:** Harmful if swallowed. Irritating to mouth, throat and stomach. May cause vomiting.

**Inhalation:** Harmful if inhaled. High concentrations of vapors in immediate area can displace oxygen and can cause dizziness, unconsciousness, and even death with longer exposure. Keep people away from such vapors without self-contained breathing apparatus.

**Pre-Existing Medical Conditions Aggravated by Exposure:** Heart, lung, skin, eye.

**SECTION 4: FIRST AID MEASURES**

**Eyes:** Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Have eyes examined and tested by medical personnel if irritation develops or persists.

**Skin:** Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists. Wash clothing separately before reuse.

**Ingestion:** Swallowing less than an ounce will not cause significant harm. For larger amounts, do not induce vomiting, but give one or two glasses of water to drink and get immediate medical attention.

**Inhalation:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

**SECTION 5: FIRE FIGHTING MEASURES**

**Flash Point:** 53°F (12C) (TCC)

**LEL/UEL:** Not established (% by volume in air)

**Extinguishing Media:** Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

**Fire Fighting Instructions:** As in any fire, wear self-contained breathing apparatus (pressure-demand, MSHA/NIOSH approved or equivalent) and full protective gear.

**SECTION 6: ACCIDENTAL RELEASE MEASURES**

**Large Spills:** Shut off leak if possible and safe to do so. Wear self-contained breathing apparatus and appropriate personal protective equipment. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container for proper disposal. Do not flush to sewer. Avoid runoff into storm sewers and ditches which lead to waterways.

**Small Spills:** Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container for proper disposal.

**SECTION 7: HANDLING AND STORAGE**

Avoid prolonged or repeated contact with eyes, skin, and clothing. Wash hands before eating. Use with adequate ventilation. Avoid breathing product vapor or mist. Do not reuse this container. Store in a cool dry place away from heat, sparks and flame. Keep container closed when not in use. Do not store in direct sunlight.

**KEEP OUT OF REACH OF CHILDREN.**

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION****Exposure Guidelines:**

| CHEMICAL NAME        | ACGIH TLV | OSHA PEL | ACGIH STEL |
|----------------------|-----------|----------|------------|
| Isopropanol          | 200ppm    | 400ppm   | 400ppm     |
| n-Propyl Acetate     | 200ppm    | 200ppm   | 250ppm     |
| Hexamethyldisiloxane | NA        | NA       | NA         |

**Work/Hygienic Practices:** Good general ventilation should be sufficient to control airborne levels. Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product. If vapor concentration exceeds TLV, use NIOSH approved organic vapor cartridge respirator. Wear safety glasses with side shields (or goggles) and rubber or other chemically resistant gloves when handling this material.

**NFPA and HMIS Codes:**

|                     | NFPA | HMIS |
|---------------------|------|------|
| Health              | 1    | 1    |
| Flammability        | 3    | 3    |
| Reactivity          | 1    | 1    |
| Personal Protection | -    | B    |

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**Physical State: Clear, colorless liquidOdor: Sweet solventpH: NAVapor Pressure: 33 mm Hg @ 68°FVapor Density: >1 @ 100°F

(Air=1)

Percent Volatile: 99.5%Solubility in Water: NegligibleSpecific Gravity: (Water =1) 0.79Evaporation Rate: <1

(Butyl acetate=1)

Viscosity: 1 (Approx.)

(Water = 1)

Boiling Point: 180 F (82C)**SECTION 10: STABILITY AND REACTIVITY**Stability: This product is stable.Conditions to Avoid: Do not spray near open flames, red hot surfaces or other sources of ignition.Incompatibility: Do not mix with powdered alkali and alkaline earth metals or strong oxidizing agents.Products of Decomposition: Thermal decomposition may release carbon monoxide, carbon dioxide and incompletely burned hydrocarbons, as well as oxides of silicone.Hazardous Polymerization: Will not occur**SECTION 11: TOXICOLOGICAL INFORMATION**Inhalation:

Isopropanol LC50/rats 12,000 ppm/8 hrs

n-Propyl Acetate TCLo/human 1,000 mg/m3

Skin:

Isopropanol Rabbit MLD

n-Propyl Acetate Rabbit 500 mg open MLD

Hexamethylsiloxane Rabbit LD50 16 mL/kg

Cancer Information: No ingredients listed as human carcinogens by NTP or IARC

Reproductive effects: none Teratogenic effects: none

Ingestion:

Isopropanol LD50/rats 5,800 mg/kg

n-Propyl Acetate LD50/rats 9,370 mg/kg

Hexamethylsiloxane LDLo rat 8 mL/kg

Eye:

n-Propyl Acetate rabbit 500 mg/24H MLD

Isopropanol rabbit MLD-MOD

Mutagenic effects: none

**SECTION 12: ECOLOGICAL INFORMATION****Environmental Impact Information**

Avoid runoff into storm sewers and ditches which lead to waterways. Water runoff can cause environmental damage.

**REPORTING**US regulations require reporting spills of this material that could reach any surface waters. The toll free number for the US Coast Guard National Response Center is: **1-800-424-8802****SECTION 13: DISPOSAL CONSIDERATIONS**

Dispose of in accordance with all federal, state and local regulations. Water runoff can cause environmental damage.

**SECTION 14: TRANSPORTATION INFORMATION**

| Proper Shipping Name                                | UN Number | Hazard Class | Sub. Risk | Pkg. Group | Hazard Label     | Pkg. Instr./Auth. | Max. Quantity |
|---|-----------|--------------|-----------|------------|------------------|-------------------|---------------|
| <u>Air:</u> Flammable liquids, n.o.s. (Isopropanol) | UN 1993   | 3            | NA        | II         | Flammable Liquid | 305               | 1L            |
| <u>Ground:</u> Consumer Commodity n.o.s. ORM-D      | NA        | --           | NA        | NA         | ORM-D            | 173.150           |               |

**SECTION 15: REGULATORY INFORMATION**SECTION 313 SUPPLIER NOTIFICATION This product contains no toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). This information should be included on all MSDSs copied and distributed for this material.TOXIC SUBSTANCES CONTROL ACT (TSCA).

All ingredients of this product are listed on the TSCA Inventory.

WHMIS: Class B2; Class D2B

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

**SECTION 16: OTHER INFORMATION**

Normal ventilation for standard manufacturing practices is usually adequate. Local exhaust should be used when large amounts are released.

To the best of our knowledge, the information contained herein is accurate. However, all materials may present unknown hazards and should be used with caution. In particular, improper use of our products and their inappropriate combination with other products and substances may produce harmful results which cannot be anticipated. Final determination of the suitability of any material is the sole responsibility of the user. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that may exist.