

**APC Performance SurgeArrest, 11 outlet, phone line (with splitter) & coax protection**


**Part Number:** P11VT3



**Output**

Number of Outlets	11
Receptacle Style	NEMA 5-15R

**Input**

Nominal Input Voltage	120V	
Input Frequency	50/60 Hz	
Input Connections	NEMA 5-15P	
Cord Length	2.44 meters	
Input Breaker Capacity	15A	

**Surge Protection and Filtering**

Surge energy rating	2030 Joules
eP Joule Rating	3400
EMI/RFI Noise rejection (100 kHz to 10 mHz)	70 dB
Data Line Protection	RJ-11 2-Way Modem/Fax/DSL splitter with protection (four wire dual lines),Cable modem / Video protection
Data Lines Protected (multi-line only)	1-4
Let Through Voltage Rating	< 40

## Physical

Net Weight	1.06 KG
Maximum Height	40.00 mm
Maximum Width	119.00 mm
Maximum Depth	302.00 mm
Shipping Weight	1.35 KG
Shipping Height	60.00 mm
Shipping Width	192.00 mm
Shipping Depth	345.00 mm
Master Carton Units	6.00
Master Carton Dimensions (Length x Width x Height)	378 x 210 x 377 mm
Master Carton Weight	8.90 KG
Color	Black

## Environmental

Operating Environment	-15 - 45 °C
Operating Relative Humidity	0%
Operating Elevation	0-3000 meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0%
Storage Elevation	0-15000 meters

## Conformance

Regulatory Approvals	CSA,UL 1363,UL 1449
Standard Warranty	Lifetime
UL 1449 TVSS Rating	330V

[Copyright](#) © American Power Conversion Corp., all rights reserved