

 Select Your Country/Region 




[Search](#)  
[Home](#)[Products](#)[Support](#)[Services](#)[Selectors](#)[How to Buy](#)

## Personal Surge Arrest 8 Outlet w/Tel 120V

Surge Protection for Personal Computers and Electronic Equipment.

Includes: 1.8 Meter Tel Cable (2), User Manual

Part Number : **PER8T**

-  [Compare Models](#)
-  [Email Technical Specifications](#)
-  [Printer Friendly](#)



[+] More Images

### Additional Information


- [Product Overview](#)
- [User Manual & Installation Guides](#)
- [Product Distribution](#)

## Technical Specifications

### Output

Number of Outlets	8
Receptacle Style	NEMA 5-15R

### Input

Nominal Input Voltage	120V
Input Frequency	50/60 Hz +/- 5 Hz (auto sensing)
Input Connections	NEMA 5-15P 
Maximum Line Current per phase	15A

### Surge Protection and Filtering

Surge energy rating	240 Joules
eP Joule Rating	1060
EMI/RFI Noise rejection (100 kHz to 10 mHz)	60 dB
Peak Current Normal Mode	6.50 kAmps
Peak Current Common Mode	13 kAmps
Dataline protection	RJ-11 Modem/Fax protection (two wire single line)
Data Lines Protected (multi-line only)	1
Let Through Voltage Rating	< 300

### Physical

Net Weight	1.80 lbs. ( 0.82 kg)
Maximum Height	1.75 inches ( 44 mm)

### Features:

- i Always on Outlets
- i Catastrophic Event Protection
- i Protection working indicator
- i Resettable circuit breaker
- i Right Angle Plug
- i Site wiring fault indicator
- i Transformer Block Spacing

Maximum Width	8.00 inches (203 mm)
Maximum depth	5.75 inches (146 mm)
Shipping Weight	2.30 lbs. ( 1.05 kg)
Shipping Height	2.00 inches ( 51 mm)
Shipping Width	12.50 inches (318 mm)
Shipping Depth	6.25 inches (159 mm)
Master Carton Units	12.00
Master Carton Weight	29.00 lbs.
SCC Codes	10731304014413
Color	Beige
Units per Pallet	600.00

## Environmental

Operating Environment	0 - 40 °C (32 - 104 °F)
Operating Relative Humidity	0 - 95%
Operating Elevation	0-10000 feet (0-3000 meters)
Storage Temperature	-15 - 45 °C (5 - 113 °F)
Storage Relative Humidity	0 - 95%
Storage Elevation	0-50000 feet (0-15000 meters)

## Conformance

Regulatory Approvals	CSA,UL 497A,UL 1283,UL 1363,UL 1449
Standard Warranty	Lifetime
UL 1449 TVSS Rating	330 V

[Copyright](#) © American Power Conversion Corp., all rights reserved  
[About APC](#)[Investors](#)[Job Seekers](#)[Press](#)[Feedback](#)[Contact](#)[Privacy Policy](#)