



Rack ATS, 15A, 100/120V, (2)5-15 in, (8)5-15 out

Part Number: AP7750

AP7750

Output

Nominal Output Voltage	100V,120V
Maximum Total Current Draw per Phase	15A
Output Connections	(8) NEMA 5-15R



Input

Nominal Input Voltage	100V,120V
Input Frequency	50/60 Hz
Regulatory Derated Input Current	12A
Input Connections	NEMA 5-15P
Cord Length	8 feet (2.44 meters)
Number of Power Cords	2
Acceptable Input Voltage	100-125 VAC
Maximum Input Current per phase	15A
Load Capacity	1440 VA



Physical

Net Weight	9.75 lbs. (4.43 kg)
Maximum Height	1.75 inches (44 mm)
Maximum Width	17.00 inches (432 mm)
Maximum depth	9.00 inches (229 mm)
Shipping Weight	16.25 lbs. (7.39 kg)
Shipping Height	2.75 inches (70 mm)
Shipping Width	23.50 inches (597 mm)
Shipping Depth	17.50 inches (445 mm)
Color	Black

Environmental

Operating Environment	23 - 113 °F (-5 - 45 °C)
Operating Relative Humidity	0 - 95%
Operating Elevation	0-10000 feet (0-3000 meters)
Storage Temperature	-13 - 149 °F (-25 - 65 °C)
Storage Relative Humidity	0 - 95%
Storage Elevation	0-50000 feet (0-15000 meters)

Conformance

Regulatory Approvals	cUL Listed,FCC Part 15 Class A,UL Listed,VCCI
Standard Warranty	2 years repair or replace

*Estimated Resale Price - Without Tax/VAT