

Super Duster 152 402B



Use for removing dust, lint and foreign particles. This product is not designed for use near ignition sources. For cleaning in such circumstances, use MG Chemicals' <u>Super Duster 134</u> (Cat. No. 402A)

- Zero residue
- Variable valve allows greater user control
- Ozone safe



HFC 152a is rated as non-flammable when subjected to the 'Test for determining the the flashback and the length of the flame projection of flammable product enclosed in a spray container' of the Canadian Hazardous Products Act. This product is not defined as flammable by 1500.3 (c)(6),16 CFR, Fed. Haz. Substance Act, C. P.S.C. Regs.

# **Available Sizes**

Catalog Number	Sizes Available	Description
402B-340G	340g (12 oz)	Aerosol
402B-450G	450g (16 oz)	Aerosol

© 2000 - 2007 MG Chemicals. All rights reserved.



# **Material Safety Data Sheet**

Section 1: Product Identification

MSDS Code: 402B - aerosol

Name: Super Duster 152

Related Part Numbers: 402B-340G, 402B-450G

Use: For removing microscopic dust.

Section 2: Hazardous Ingredients					
CAS#	Chemical Name	Percentage by weight	ACGIH TWA	Osha Pel	Osha Stel
75-37-6	1,1-Difluoroethane	99%	n/e	n/e	n/e

# **Section 3: Hazards Identification**

WHMIS Codes: A			
NFPA Ratings:	Health 1 Flammability 4 Reactivity 1		
HMIS Ratings:	Health 1 Flammability 4 Reactivity 1		
Eyes:	Contact with eye may cause severe tissue damage because of frostbite.		
Skin:	Contact with liquid or escaping vapor can cause frostbite, indicated by pallor or redness, loss of sensation, and swelling.		
Inhalation:	Deliberate Inhalation of high concentrations of vapor should be avoided as it is harmful. Deliberate inhalation, may result in cardiac symptoms, unconsciousness or death. This product is not recommended for intentional misuse or deliberate inhalation as death without warning may occur. When oxygen levels in air are reduced to 12% - 14% symptoms of asphyxiation will occur: loss of coordination, increased pulse rate, and deeper respiration.		
Ingestion:	Aspiration hazard. May cause irritation of the digestive tract.		
Chronic:	Over exposure may cause dizziness and loss of concentration. At higher levels, CNS depression and cardiac arrhythmia may result from exposure.		

#### Section 4: First Aid Measure

Eyes:	Immediately bathe (do not rub) any frostbite with lukewarm (not hot) water. In the absence of water, cover with soft wool or other suitable material. Contact a physician for any low temperature burns from liquid contact.
Skin:	Immediately bathe (do not rub) any frostbite with lukewarm (not hot) water. In the absence of water, cover with soft wool or other suitable material. Contact a physician for any low temperature burns from liquid contact.
Inhalation:	Immediately remove from exposure to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical aid.
Ingestion:	Improbable due to low boiling point (-25°C).



### Section 5: Fire Fighting Measures

Autoignition Temperature:	454°C	Flash Point: -50°C	LEL / UEL: 3.9/16.9
Extinguishing Media:	Use water spray, dry chemical, carbon dioxide, or chemical foam.		
General Information:	WARNING: Do not hake or tilt during use as flammable liquid may be dispensed. In not use near potential sources of ignition, open flames, hot surfaces or live electrical appliances. Containers may explode in the heat of a fire.		

#### Section 6: Accidental Release Measures

**Spill Procedure:** Avoid breathing vapors. Ventilate area thoroughly.

#### Section 7: Handling and Storage

Handling: Avoid contact with eyes, skin, and clothing. Do not inhale. Do not expose container to heat or flame.

Storage: Keep away from direct sunlight, heat, and sources of ignition. Store in a cool, dry, well ventilated area.

## **Section 8: Exposure Controls**

Routes of entry:	Eyes, ingestion, inhalation, and skin.
Ventilation:	Use adequate general or local exhaust ventilation to keep airborne concentrations below exposure limits.
Personal Protection:	Wear appropriate protective eyeglasses or chemical safety goggles. Wear appropriate protective clothing to prevent skin contact. Use a NIOSH approved respirator when necessary.

#### Section 9: Physical and Chemical Properties

Physical State:	Gas	Odor:	ethereal	Solubility:	0.27%	Evaporation Rate:	1 (ether=1)		
Boiling Point:	-26.2°C	Specific Gravity:	0.99g/cc	Vapor Pressure:	86 PSI @21°C	Vapor Density:	2.4(Air=1)	pH:	7

## Section 10: Stability and Reactivity

Stability:	Stable at normal temperatures and pressures. Do not mix with oxygen or air above atmospheric pressure. Any source of high temperature, such as lit cigarettes, flames, or welding may yield toxic and/or corrosive decomposition products.	
Conditions to avoid:	Temperatures over 40°C, ignition sources, and incompatible materials.	
Incompatibilities:	Alkali and alkaline earth metals, powdered aluminum, zinc, magnesium, and beryllium.	
Polymerization:	Will not occur.	
Decomposition:	Halogens, halogen acids, possibly carbonyl halides. This material can decompose at high temperatures.	

#### Section 11: Toxicological Information

Sensitization: (effects of repeated exposure)	No effects known. Cardiac sensitization occurred in dogs exposed to 150,000 ppm.
<b>Carcinogenicity</b> : (risk of cancer)	The ingredients of this product are not classified as being carcinogenic by ACGIH (American Conference of Governmental industrial Hygienists) or IARC (International Agency for Research on Cancer), not regulated as carcinogens by OSHA (Occupational Safety and Health Administration), and not listed as carcinogens by NTP (National Toxicology Program)



Teratogenicity: (risk of malformation in an unborn fetus)	N/e		
Reproductive Toxicity: (risk of sterility)	N/e		
Mutangenicity: (risk of heritable genetic effects)	Unknown		
Lethal Exposure Concentrations:	Ingestion(LD50): n/e	Inhalation(LC50): N/e	Skin(LD50): n/e

#### Section 12: Ecological Information

Avoid runoff into storms and sewers, which lead into waterways. Water runoff can cause **General Information:** environmental damage. Environmental Impact Data: (percentage by weight)

**CFC**: 0 HFC: 100

**CI.Solv**.: 0

**HCFC:** 0 **ODP**: 0

## Section 13: Disposal Information

General Information:

Dispose of in accordance with all local, provincial, state, and federal regulations. Water runoff can cause environmental damage.

**VOC**: 0

## Section 14: Transportation Information

#### Ground:

Consumer Commodity, ORM-D

#### Air:

Cannot be shipped by air.

#### Sea:

Limited quantity, 1,1-Difluoroethane, UN#1030, Class 2.1. Shipper must be trained and certified. Refer to IMDG regulations.

# Section 15: Regulatory Information

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all of the information required by the Controlled Products Regulations.

SARA (Superfund Amendments and Reauthorization Act of 1986, USA, 40CFR 372.4)

None of the chemicals in this product have a reportable quantity.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45

This product does not contain any chemicals subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

# Section 15: Regulatory Information Cont'd

## CAA (Clean Air Act, USA)

This product does not contain any class 1 ozone depletors.

This product does not contain any class 2 ozone depletors.

This product does not contain any chemicals listed as hazardous air pollutants.