Panel Mount Indicator, Non-Relampable
Neon Technology
Mounting Hole, Ø 0.500”



All dimensions are in inches

RoHS COMPLIANT

Recommended panel thickness: 0.030” to 0.090”

.187 terminals are standard

Storage temperature T_{STG} : -25°C - +80°C
Ambient temperature T_A : -20°C - +60°C
Voltage tolerance V_{OP} : ±10%

Part No.	*Lens Color*	*Voltage*	*Current mA*	*Rated Life*
Neon 115VAC Series				
WL-1050QA1	Red	105-125VAC	1.5mA	25,000 Hrs
WL-1050QA2	Clear	105-125VAC	1.5mA	25,000 Hrs
WL-1050QA3	Amber	105-125VAC	1.5mA	25,000 Hrs
WL-1050QA4	White	105-125VAC	1.5mA	25,000 Hrs
WL-1052QA5	Green	105-125VAC	1.5mA	25,000 Hrs
WL-1052QA6	Blue	105-125VAC	1.5mA	25,000 Hrs
Neon 230VAC Series				
WL-1051QA1	Red	208-250VAC	1.5mA	25,000 Hrs
WL-1051QA3	Amber	208-250VAC	1.5mA	25,000 Hrs
WL-1051QA4	White	208-250VAC	1.5mA	25,000 Hrs
WL-1053QA5	Green	208-250VAC	1.5mA	25,000 Hrs
WL-1053QA6	Blue	208-250VAC	1.5mA	25,000 Hrs

Body Material: Nylon, white
Lens Material: Polycarbonate
Bezel Material: Stainless steel
Note: .250 quick connects available upon request

Certifications: Most Wamco indicators carry Agency approvals. Please contact Wamco for the latest Agency information regarding the specific product series and voltage required.

Options: Additional options and lens styles available. Please contact Wamco for more information.

Drawn	SC	03/01/10	**Panel Mount Indicators Neon**	**Datasheet:** WL-105XQAX Series	**Rev:** 1
Checked	EB	03/01/10			
Approved	EB	03/02/10			

11555 Coley River Circle
Fountain Valley, CA 92708
714.545.5560
Fax: 714.545.6093
www.wamcoinc.com
info@wamcoinc.com

Downloaded from Elcodis.com electronic components distributor