




CML INNOVATIVE TECHNOLOGIES
WHERE INNOVATION COMES TO LIGHT

Products

LED Indicators

CML IT offers panel mount indicators manufactured with LED, Neon or Incandescent light sources. These indicators are available in a number of different lens and termination styles, with voltages of 2V ~ 250V available off-the-shelf.



Part Number: 19710350
Serial Number: 1971
Mounting hole (inch): 0.7480"
Mounting hole (metric): 19mm
Indicator type: standard
Mounting type: with bezel
Bezel type: prominent
Bezel material: metal
Bezel color: satin chrome
Bezel size: M19
Protection: IP67
Lens type: flat
Lens color: red diffused
Lens size: 10mm
Connector tpe: tab terminals 2.8x0.8
Connector number: 2
Connector for lamp test: no
Number LED chip: 1
Indicator color: red
Dom wave length: 630nm
Peak wave length (mA):
Op. voltage (V): 24V AC/DC
Forward volt max:
Rectifier: Half Wave
AC current: 8mA
DC current: 16mA
Lum in min (mcd):
Lum in type (DC): 1500mcd
Voltage type (%): 10%
Op. temperature (°C): -25 °C - +60 °C
Storage temperature (°C): -25°C - +60°C
Narrative:
Viewing angle (°):
RoHS Status: Yes