

**Item # 710-0003 Model 710 Electromechanical Hour Meter**



**Model 710 Electromechanical Hour Meter**

The Model 710 AC hour meters and minute meters are widely used in panel applications where number size and visibility are critical. Its tough, Lexan bezel and distinctive styling enhance appearance and durability. Available in 5 figures reset or 6 figures non-reset versions.

**Specifications**

<b>Model No.</b>	710
<b>Mounting</b>	Panel (3-Hole)
<b>Reset</b>	Non-reset
<b>Termination</b>	8 inch (203mm) wire leads
<b>Display</b>	6 figures, 99999.9 (non-reset), 0.19 inch (5mm) high
<b>Display Height</b>	0.19 Inch
<b>Display Height</b>	5 mm
<b>No. of Digits</b>	6
<b>Records</b>	99999.9 hours
<b>Input Voltage</b>	230 VAC 60 Hz $\pm$ 10%
<b>Power</b>	3 watts (nominal)
<b>Operating Temperature</b>	-20 to +160 °F
<b>Operating Temperature</b>	-29 to +71 °C
<b>Weight</b>	6 oz
<b>Weight</b>	170 gm
<b>Panel Cutout</b>	2.21 Inch
<b>Panel Cutout</b>	56.1 mm
<b>Mounting Holes</b>	For No. 4 screws on 2.44 inch (62.0mm) B.C. and No. 6 screws on 2.53 inch (64.3mm) B.C.
<b>Approvals</b>	UL Recognized, CSA Certified, CE Compliant
<b>Stock Availability</b>	Yes



## Description

The model 710 AC hour meters and minute meters are widely used in panel applications where number size and visibility are critical. Its tough, Lexan bezel and distinctive styling enhance appearance and durability. Available in 5 figure reset or 6 figure non-reset versions.

## Features

- Large figures
- Tough, Lexan case
- Reset or non-reset

## Options

- Private label faceplates
- Bracket mount
- Mounting bracket (721-0003)
- Splash proof kit (721-0017)
- Heavy duty splash proof kit (721-0018)
- Gasket (721-0004)

## Specifications

**Figures:** 5 figures, 9999.9 (reset) or 6 figure, 99999.9 (non-reset), 0.19" [5mm] high  
**Reset:** Reset (on front or side) or non-reset  
**Voltages:** 24, 115 or 230VAC, (+/-10%), 50 or 60 Hz.  
**Power:** 3 watts (nominal)  
**Mounting:** Panel (3-hole)


**Terminations:** 8" [203.2mm] wire leads or terminal block  
**Temp. Range:** -20°F to +160°F [-29°C to +71°C]  
**Approvals:** UL Recognized, CSA Certified, CE Compliant  
**Weight:** 6 oz. [170g]

Models	Description	Models	Description
<b>710-0001</b>	115VAC/60Hz, non-reset, 99,999.9 hrs, 8" [203mm] wire leads	<b>710-0014</b>	230VAC/60Hz, non-reset, 99,999.9 hrs, terminal block
<b>710-0002</b>	115VAC/60Hz, non-reset, 99,999.9 hrs, terminal block	710-0018	115VAC/60Hz, non-reset, 99,999.9 min, 8" [203mm] wire leads
<b>710-0003</b>	230VAC/60Hz, non-reset, 99,999.9 hrs, 8" [203mm] wire leads	710-0024	24VAC/60Hz, non-reset, 99,999.9 hrs, terminal block
<b>710-0006</b>	24VAC/60Hz, non-reset, 99,999.9 hrs, 8" [203mm] wire leads	<b>710-0026</b>	115VAC/50Hz, non-reset, 99,999.9 hrs, terminal block
710-0008	115VAC/60Hz, non-reset, 99,999 hrs, 8" [203mm] wire leads	<b>710-0032</b>	115VAC/60Hz, front reset, 9,999.9 hrs, terminal block
<b>710-0009</b>	115VAC/50Hz, non-reset, 99,999.9 hrs, 8" [203mm] wire leads	710-0051	115VAC/60Hz, non-reset, 99,999 hrs, terminal block
<b>710-0013</b>	115VAC/60Hz, front reset, 9,999.9 hrs, 8" [203mm] wire leads		

\* Items in bold are normally in factory stock.

## Dimensions

### 8" [203mm] Wire Leads



Mounting holes: For #4 screws on 2.44" [62.0] B.C.  
and #6 screws on 2.53" [64.3] B.C.  
Panel cutout: 2.21" [56.1] Dia.

## Applications


Office equipment



Control panels



Industrial equipment



Test equipment



Compressors

