

SEARCH OUR PRODUCTS


aluminum electrolytic & organic semiconductor


film


power film

 
tantalum ceramic



Aluminum Electrolytic Capacitors

+85°C Standard Radial Lead Aluminum Electrolytic Capacitors

Part Number: 477CKS063M

[General Specifications \(PDF\)](#)

[Special Order Options](#)

[CKR_CKS document \(PDF\)](#)



Electrical Specifications

Capacitance: 470.0 μ F
Tolerance: -20 %, +20 %
Dissipation Factor: 0.1 at 120 Hz
ESR: 0.353 Ohms at 20° C and 120 Hz
Impedance:
 --
 --

Temperature Range: -40°C to +85°C
WVDC: 63 volts DC
SVDC: 79. volts DC
Leakage Current:
 888.0 μ A after 1 Minute
Ripple Current:
 900.0 mA at 120 Hz and 85°C

Impedance Ratios:

2.0 at -25°C/20°C
 3.0 at -40°C/20°C

Load Life:

2000 Hours at 85°C with 100% of rated voltage and with 0% of rated ripple current

Physical Specifications

Diameter (D): 12.5 mm + 0.5 mm
Length (L): 20.0 mm + 1.5 mm
Lead Wire Diameter (d): 0.6 mm + 0.05 mm
Lead Spacing: 5.0 mm +/- 0.5 mm
Lead Length: 15 mm

