



Voltage	Switching Freq. (Hz)	Operating Current (mA)	Operating Temp. (°C)	Protection	Housing	Face	End Cap	Power LED	Output LED	Cable Length/ Cable Mat.	Wiring Diagram #	Wiring Diagrams
10-30 VDC	2000	≤200	-40 to +70	IP 68/ 69 K	SS	PVDF	EPTR	N/A	YE	2M/PUR	3	<p>Diagram 1</p>
	1000	≤100	-25 to +70	IP 67	CPB	PA 12	EPTR	N/A	YE	2M/PVC	1	<p>Diagram 2</p>
10-30 VDC	3000	≤200	-30 to +85	IP 68	SS	PA 12	EPTR	N/A	YE	2M/PVC	2	<p>Diagram 3</p>
	3000	≤200	-30 to +85	IP 67	CPB	PA 12	EPTR	N/A	YE	2M/PVC	2	
10-30 VDC	3000	≤200	-30 to +85	IP 68	SS	PA 12	EPTR	N/A	YE	2M/PVC	3	<p>Diagram 4</p>
	3000	≤200	-30 to +85	IP 67	CPB	PA 12	EPTR	N/A	YE	2M/PVC	3	
10-30 VDC	2000	≤200	-25 to +70	IP 67	CPB	PA 12	EPTR	N/A	YE	2M/PVC	4	<p>Diagram 5</p>
	2000	≤200	-25 to +70	IP 67	CPB	PA 12	EPTR	N/A	YE	2M/PVC	4	
10-30 VDC	2000	≤200	-25 to +70	IP 67	CPB	PA 12	EPTR	N/A	YE	2M/PVC	5	
10-30 VDC	100	≤200	-25 to +120	IP 67	SS	PTFE	PTFE	N/A	N/A	2M/PTFE	3	
	10-30 VDC	2000	≤200	-25 to +70	IP 67	CPB	PA 12	EPTR	N/A	YE	2M/PVC	2
10-30 VDC	2000	≤200	-25 to +70	IP 67	CPB	PA 12	EPTR	N/A	YE	2M/PVC	2	
	10-30 VDC	2000	≤200	-25 to +70	IP 67	CPB	PA 12	EPTR	N/A	YE	2M/PVC	2
10-30 VDC	2000	≤200	-25 to +70	IP 67	CPB	PA 12	EPTR	N/A	YE	2M/PVC	3	
	1500	≤200	-25 to +70	IP 67	CPB	PA 12	EPTR	N/A	YE	2M/PVC	3	
	2000	≤200	-25 to +70	IP 67	CPB	PA 12	EPTR	N/A	YE	2M/PVC	3	

Barrels

For material descriptions see page M22.

Inductive Sensors



Housing Style	Part Number	ID Number	Features	Sensing Range (mm)	Output
12 mm - Embeddable, Potted-In Cable 	Bi 3-GT12K-AD4X/S1610	T4405083-2	<i>armorguard</i>	3	2-Wire DC
	Bi 2-EG12HK-AN6X/S1589	T4605192	<i>armorguard</i>	2	3-Wire DC NPN
	Bi 2-G12K-AN6X	T4671200	<i>Short Barrel</i>	2	
	Bi 4-G12K-AN6X	T4670251	<i>Short Barrel</i>	4	
	Bi 2-G12K-AP6X	T4670200	<i>Short Barrel</i>	2	3-Wire DC PNP
	Bi 4-G12K-AP6X	T4670250	<i>Short Barrel</i>	4	
	Bi 2-EG12-Y0X	T4012000		2	2-Wire DC NAMUR
	Bi 2-G12-Y0	T1005400		2	
	Bi 2-G12-Y0X	T4010000		2	
	12 mm - Embeddable, Potted-In Cable 	Bi 2-EG12-AN6X	T4605101		2
Bi 2-G12-AN6X		T4635500		2	
Bi 2-G12-AN7X		T4730500	<i>TTL Compatible</i>	2	
Bi 4-G12-AN6X		T1690706	<i>Extended Range</i>	4	
Bi 2-EG12-AP6X		T4605001		2	3-Wire DC PNP
Bi 2-G12-AP6X		T4635400		2	
12 mm - Embeddable, Potted-In Cable 	Bi 2-G12-ADZ32X	T4205000		2	2-Wire AC/DC Short-circuit Protected
	Bi 4-G12-ADZ32X	T4205030	<i>Extended Range</i>	4	
	Bi 2-G12-AZ33X	T1304002		2	2-Wire AC/DC
	Bi 2-GT12-ADZ32X/S34	T4205210	<i>WFI</i>	2	2-Wire AC/DC Short-circuit Protected
12 mm - Embeddable, Potted-In Cable, Teflon Coated 	Bi 2-GT12-AZ33X/S34	T1304052	<i>WFI</i>	2	2-Wire AC/DC

For detailed sensor specifications see Section M.
Normally Closed versions available upon request, consult factory.