

## Rail-to-Rail Input/Output, 10 MHz Op Amps

### Features

- Rail-to-Rail Input/Output
- Wide Bandwidth: 10 MHz (typ.)
- Low Noise: 8.7 nV/√Hz, at 10 kHz (typ.)
- Low Offset Voltage:
  - Industrial Temperature: ±500 μV (max.)
  - Extended Temperature: ±250 μV (max.)
- Mid-Supply  $V_{REF}$ : MCP6021 and MCP6023
- Low Supply Current: 1 mA (typ.)
- Total Harmonic Distortion: 0.00053% (typ., G = 1)
- Unity Gain Stable
- Power Supply Range: 2.5V to 5.5V
- Temperature Range:
  - Industrial: -40°C to +85°C
  - Extended: -40°C to +125°C


### Typical Applications

- Automotive
- Driving A/D Converters
- Multi-Pole Active Filters
- Barcode Scanners
- Audio Processing
- Communications
- DAC Buffer
- Test Equipment
- Medical Instrumentation

### Available Tools

- SPICE Macro Model (at [www.microchip.com](http://www.microchip.com))
- FilterLab<sup>®</sup> software (at [www.microchip.com](http://www.microchip.com))

### Typical Application




### Description

The MCP6021, MCP6021R, MCP6022, MCP6023 and MCP6024 from Microchip Technology Inc. are rail-to-rail input and output op amps with high performance. Key specifications include: wide bandwidth (10 MHz), low noise (8.7 nV/√Hz), low input offset voltage and low distortion (0.00053% THD+N). The MCP6023 also offers a Chip Select pin ( $\overline{CS}$ ) that gives power savings when the part is not in use.

The single MCP6021 and MCP6021R are available in SOT-23-5. The single MCP6021, single MCP6023 and dual MCP6022 are available in 8-lead PDIP, SOIC and TSSOP. The Extended Temperature single MCP6021 is available in 8-lead MSOP. The quad MCP6024 is offered in 14-lead PDIP, SOIC and TSSOP packages.

The MCP6021/1R/2/3/4 family is available in Industrial and Extended temperature ranges. It has a power supply range of 2.5V to 5.5V.

### Package Types



# MCP6021/1R/2/3/4

## 1.0 ELECTRICAL CHARACTERISTICS

### Absolute Maximum Ratings †

|   |   |
|---|---|
| $V_{DD} - V_{SS}$ .....                   | 7.0V  |
| All Inputs and Outputs .....              | $V_{SS} - 0.3V$ to $V_{DD} + 0.3V$              |
| Difference Input Voltage .....            | $ V_{DD} - V_{SS} $                             |
| Output Short Circuit Current .....        | continuous                                      |
| Current at Input Pins .....               | $\pm 2$ mA                                      |
| Current at Output and Supply Pins .....   | $\pm 30$ mA                                     |
| Storage Temperature.....                  | $-65^{\circ}\text{C}$ to $+150^{\circ}\text{C}$ |
| Junction Temperature.....                 | $+150^{\circ}\text{C}$                          |
| ESD Protection on all pins (HBM; MM)..... | $\geq 2$ kV; 200V                               |

† **Notice:** Stresses above those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress rating only and functional operation of the device at those or any other conditions above those indicated in the operational listings of this specification is not implied. Exposure to maximum rating conditions for extended periods may affect device reliability.

### DC ELECTRICAL CHARACTERISTICS

**Electrical Specifications:** Unless otherwise indicated,  $T_A = +25^{\circ}\text{C}$ ,  $V_{DD} = +2.5\text{V}$  to  $+5.5\text{V}$ ,  $V_{SS} = \text{GND}$ ,  $V_{CM} = V_{DD}/2$ ,  $V_{OUT} \approx V_{DD}/2$  and  $R_L = 10$  k $\Omega$  to  $V_{DD}/2$ .

| Parameters  | Sym                         | Min          | Typ          | Max          | Units                          | Conditions   |
|---|-----------------------------|--------------|--------------|--------------|--------------------------------|--|
| <b>Input Offset</b>                                 |                             |              |              |              |                                |  |
| Input Offset Voltage:                               |                             |              |              |              |                                |  |
| Industrial Temperature Parts                        | $V_{OS}$                    | -500         | —            | +500         | $\mu\text{V}$                  | $V_{CM} = 0\text{V}$   |
| Extended Temperature Parts                          | $V_{OS}$                    | -250         | —            | +250         | $\mu\text{V}$                  | $V_{CM} = 0\text{V}$ , $V_{DD} = 5.0\text{V}$  |
| Extended Temperature Parts                          | $V_{OS}$                    | -2.5         | —            | +2.5         | mV                             | $V_{CM} = 0\text{V}$ , $V_{DD} = 5.0\text{V}$<br>$T_A = -40^{\circ}\text{C}$ to $+125^{\circ}\text{C}$ |
| Input Offset Voltage Temperature Drift              | $\Delta V_{OS}/\Delta T_A$  | —            | $\pm 3.5$    | —            | $\mu\text{V}/^{\circ}\text{C}$ | $T_A = -40^{\circ}\text{C}$ to $+125^{\circ}\text{C}$  |
| Power Supply Rejection Ratio                        | PSRR                        | 74           | 90           | —            | dB                             | $V_{CM} = 0\text{V}$   |
| <b>Input Current and Impedance</b>                  |                             |              |              |              |                                |  |
| Input Bias Current                                  | $I_B$                       | —            | 1            | —            | pA                             |  |
| Industrial Temperature Parts                        | $I_B$                       | —            | 30           | 150          | pA                             | $T_A = +85^{\circ}\text{C}$  |
| Extended Temperature Parts                          | $I_B$                       | —            | 640          | 5,000        | pA                             | $T_A = +125^{\circ}\text{C}$   |
| Input Offset Current                                | $I_{OS}$                    | —            | $\pm 1$      | —            | pA                             |  |
| Common-Mode Input Impedance                         | $Z_{CM}$                    | —            | $10^{13}  6$ | —            | $\Omega  \text{pF}$            |  |
| Differential Input Impedance                        | $Z_{DIFF}$                  | —            | $10^{13}  3$ | —            | $\Omega  \text{pF}$            |  |
| <b>Common-Mode</b>                                  |                             |              |              |              |                                |  |
| Common-Mode Input Range                             | $V_{CMR}$                   | $V_{SS}-0.3$ | —            | $V_{DD}+0.3$ | V                              |  |
| Common-Mode Rejection Ratio                         | CMRR                        | 74           | 90           | —            | dB                             | $V_{DD} = 5\text{V}$ , $V_{CM} = -0.3\text{V}$ to $5.3\text{V}$  |
|   | CMRR                        | 70           | 85           | —            | dB                             | $V_{DD} = 5\text{V}$ , $V_{CM} = 3.0\text{V}$ to $5.3\text{V}$   |
|   | CMRR                        | 74           | 90           | —            | dB                             | $V_{DD} = 5\text{V}$ , $V_{CM} = -0.3\text{V}$ to $3.0\text{V}$  |
| <b>Voltage Reference (MCP6021 and MCP6023 only)</b> |                             |              |              |              |                                |  |
| $V_{REF}$ Accuracy ( $V_{REF} - V_{DD}/2$ )         | $V_{REF\_ACC}$              | -50          | —            | +50          | mV                             |  |
| $V_{REF}$ Temperature Drift                         | $\Delta V_{REF}/\Delta T_A$ | —            | $\pm 100$    | —            | $\mu\text{V}/^{\circ}\text{C}$ | $T_A = -40^{\circ}\text{C}$ to $+125^{\circ}\text{C}$  |
| <b>Open-Loop Gain</b>                               |                             |              |              |              |                                |  |
| DC Open-Loop Gain (Large Signal)                    | $A_{OL}$                    | 90           | 110          | —            | dB                             | $V_{CM} = 0\text{V}$ ,<br>$V_{OUT} = V_{SS}+0.3\text{V}$ to $V_{DD}-0.3\text{V}$                       |
| <b>Output</b>                                       |                             |              |              |              |                                |  |
| Maximum Output Voltage Swing                        | $V_{OL}$ , $V_{OH}$         | $V_{SS}+15$  | —            | $V_{DD}-20$  | mV                             | 0.5V output overdrive  |
| Output Short Circuit Current                        | $I_{SC}$                    | —            | $\pm 30$     | —            | mA                             | $V_{DD} = 2.5\text{V}$   |
|   | $I_{SC}$                    | —            | $\pm 22$     | —            | mA                             | $V_{DD} = 5.5\text{V}$   |
| <b>Power Supply</b>                                 |                             |              |              |              |                                |  |
| Supply Voltage                                      | $V_S$                       | 2.5          | —            | 5.5          | V                              |  |
| Quiescent Current per Amplifier                     | $I_Q$                       | 0.5          | 1.0          | 1.35         | mA                             | $I_O = 0$  |

## AC ELECTRICAL CHARACTERISTICS

**Electrical Specifications:** Unless otherwise indicated,  $T_A = +25^\circ\text{C}$ ,  $V_{DD} = +2.5\text{V}$  to  $+5.5\text{V}$ ,  $V_{SS} = \text{GND}$ ,  $V_{CM} = V_{DD}/2$ ,  $V_{OUT} \approx V_{DD}/2$ ,  $R_L = 10\text{ k}\Omega$  to  $V_{DD}/2$  and  $C_L = 60\text{ pF}$ .

| Parameters   | Sym          | Min | Typ     | Max | Units                        | Conditions   |
|--|--------------|-----|---------|-----|------------------------------|--|
| <b>AC Response</b>   |              |     |         |     |                              |  |
| Gain Bandwidth Product                                       | GBWP         | —   | 10      | —   | MHz                          |  |
| Phase Margin at Unity-Gain                                   | PM           | —   | 65      | —   | °                            | $G = +1$   |
| Settling Time, 0.2%  | $t_{SETTLE}$ | —   | 250     | —   | ns                           | $G = +1$ , $V_{OUT} = 100\text{ mV}_{p-p}$   |
| Slew Rate  | SR           | —   | 7.0     | —   | V/ $\mu\text{s}$             |  |
| <b>Total Harmonic Distortion Plus Noise</b>                  |              |     |         |     |                              |  |
| $f = 1\text{ kHz}$ , $G = +1\text{ V/V}$                     | THD+N        | —   | 0.00053 | —   | %                            | $V_{OUT} = 0.25\text{V}$ to $3.25\text{V}$ ( $1.75\text{V} \pm 1.50\text{V}_{PK}$ ), $V_{DD} = 5.0\text{V}$ , $BW = 22\text{ kHz}$ |
| $f = 1\text{ kHz}$ , $G = +1\text{ V/V}$ , $R_L = 600\Omega$ | THD+N        | —   | 0.00064 | —   | %                            | $V_{OUT} = 0.25\text{V}$ to $3.25\text{V}$ ( $1.75\text{V} \pm 1.50\text{V}_{PK}$ ), $V_{DD} = 5.0\text{V}$ , $BW = 22\text{ kHz}$ |
| $f = 1\text{ kHz}$ , $G = +1\text{ V/V}$                     | THD+N        | —   | 0.0014  | —   | %                            | $V_{OUT} = 4\text{V}_{P-P}$ , $V_{DD} = 5.0\text{V}$ , $BW = 22\text{ kHz}$  |
| $f = 1\text{ kHz}$ , $G = +10\text{ V/V}$                    | THD+N        | —   | 0.0009  | —   | %                            | $V_{OUT} = 4\text{V}_{P-P}$ , $V_{DD} = 5.0\text{V}$ , $BW = 22\text{ kHz}$  |
| $f = 1\text{ kHz}$ , $G = +100\text{ V/V}$                   | THD+N        | —   | 0.005   | —   | %                            | $V_{OUT} = 4\text{V}_{P-P}$ , $V_{DD} = 5.0\text{V}$ , $BW = 22\text{ kHz}$  |
| <b>Noise</b>   |              |     |         |     |                              |  |
| Input Noise Voltage  | $E_{ni}$     | —   | 2.9     | —   | $\mu\text{V}_{p-p}$          | $f = 0.1\text{ Hz}$ to $10\text{ Hz}$  |
| Input Noise Voltage Density                                  | $e_{ni}$     | —   | 8.7     | —   | $\text{nV}/\sqrt{\text{Hz}}$ | $f = 10\text{ kHz}$  |
| Input Noise Current Density                                  | $i_{ni}$     | —   | 3       | —   | $\text{fA}/\sqrt{\text{Hz}}$ | $f = 1\text{ kHz}$   |

## MCP6023 CHIP SELECT ( $\overline{\text{CS}}$ ) ELECTRICAL CHARACTERISTICS

**Electrical Specifications:** Unless otherwise indicated,  $T_A = +25^\circ\text{C}$ ,  $V_{DD} = +2.5\text{V}$  to  $+5.5\text{V}$ ,  $V_{SS} = \text{GND}$ ,  $V_{CM} = V_{DD}/2$ ,  $V_{OUT} \approx V_{DD}/2$ ,  $R_L = 10\text{ k}\Omega$  to  $V_{DD}/2$  and  $C_L = 60\text{ pF}$ .


| Parameters  | Sym           | Min          | Typ   | Max          | Units         | Conditions   |
|---|---------------|--------------|-------|--------------|---------------|--|
| <b><math>\overline{\text{CS}}</math> Low Specifications</b>     |               |              |       |              |               |  |
| $\overline{\text{CS}}$ Logic Threshold, Low                     | $V_{IL}$      | $V_{SS}$     | —     | $0.2 V_{DD}$ | V             |  |
| $\overline{\text{CS}}$ Input Current, Low                       | $I_{CSL}$     | -1.0         | 0.01  | —            | $\mu\text{A}$ | $\overline{\text{CS}} = V_{SS}$  |
| <b><math>\overline{\text{CS}}</math> High Specifications</b>    |               |              |       |              |               |  |
| $\overline{\text{CS}}$ Logic Threshold, High                    | $V_{IH}$      | $0.8 V_{DD}$ | —     | $V_{DD}$     | V             |  |
| $\overline{\text{CS}}$ Input Current, High                      | $I_{CSH}$     | —            | 0.01  | 2.0          | $\mu\text{A}$ | $\overline{\text{CS}} = V_{DD}$  |
| GND Current   | $I_{SS}$      | -2           | -0.05 | —            | $\mu\text{A}$ | $\overline{\text{CS}} = V_{DD}$  |
| Amplifier Output Leakage  | $I_{O(LEAK)}$ | —            | 0.01  | —            | $\mu\text{A}$ | $\overline{\text{CS}} = V_{DD}$  |
| <b><math>\overline{\text{CS}}</math> Dynamic Specifications</b> |               |              |       |              |               |  |
| $\overline{\text{CS}}$ Low to Amplifier Output Turn-on Time     | $t_{ON}$      | —            | 2     | 10           | $\mu\text{s}$ | $G = +1$ , $V_{IN} = V_{SS}$ , $\overline{\text{CS}} = 0.2V_{DD}$ to $V_{OUT} = 0.45V_{DD}$ time |
| $\overline{\text{CS}}$ High to Amplifier Output High-Z Time     | $t_{OFF}$     | —            | 0.01  | —            | $\mu\text{s}$ | $G = +1$ , $V_{IN} = V_{SS}$ , $\overline{\text{CS}} = 0.8V_{DD}$ to $V_{OUT} = 0.05V_{DD}$ time |
| Hysteresis  | $V_{HYST}$    | —            | 0.6   | —            | V             | $V_{DD} = 5.0\text{V}$ , Internal Switch   |

# MCP6021/1R/2/3/4

## TEMPERATURE CHARACTERISTICS

| Electrical Specifications: Unless otherwise indicated, $V_{DD} = +2.5V$ to $+5.5V$ and $V_{SS} = GND$ . |               |     |     |      |       |               |
|---|---------------|-----|-----|------|-------|---------------|
| Parameters  | Sym           | Min | Typ | Max  | Units | Conditions    |
| <b>Temperature Ranges</b>   |               |     |     |      |       |               |
| Industrial Temperature Range  | $T_A$         | -40 | —   | +85  | °C    |               |
| Extended Temperature Range  | $T_A$         | -40 | —   | +125 | °C    |               |
| Operating Temperature Range   | $T_A$         | -40 | —   | +125 | °C    | <b>Note 1</b> |
| Storage Temperature Range   | $T_A$         | -65 | —   | +150 | °C    |               |
| <b>Thermal Package Resistances</b>  |               |     |     |      |       |               |
| Thermal Resistance, 5L-SOT-23   | $\theta_{JA}$ | —   | 256 | —    | °C/W  |               |
| Thermal Resistance, 8L-PDIP   | $\theta_{JA}$ | —   | 85  | —    | °C/W  |               |
| Thermal Resistance, 8L-SOIC   | $\theta_{JA}$ | —   | 163 | —    | °C/W  |               |
| Thermal Resistance, 8L-MSOP   | $\theta_{JA}$ | —   | 206 | —    | °C/W  |               |
| Thermal Resistance, 8L-TSSOP  | $\theta_{JA}$ | —   | 124 | —    | °C/W  |               |
| Thermal Resistance, 14L-PDIP  | $\theta_{JA}$ | —   | 70  | —    | °C/W  |               |
| Thermal Resistance, 14L-SOIC  | $\theta_{JA}$ | —   | 120 | —    | °C/W  |               |
| Thermal Resistance, 14L-TSSOP   | $\theta_{JA}$ | —   | 100 | —    | °C/W  |               |


**Note 1:** The industrial temperature devices operate over this extended temperature range, but with reduced performance. In any case, the internal junction temperature ( $T_J$ ) must not exceed the absolute maximum specification of 150°C.



**FIGURE 1-1:** Timing diagram for the  $\overline{CS}$  pin on the MCP6023.

# MCP6021/1R/2/3/4

## 8-Lead Plastic Small Outline (SN) – Narrow, 150 mil (SOIC)



| Dimension                | Units | INCHES* |      |      | MILLIMETERS |      |      |
|--------------------------|-------|---------|------|------|-------------|------|------|
|                          |       | MIN     | NOM  | MAX  | MIN         | NOM  | MAX  |
| Number of Pins           | n     |         | 8    |      |             | 8    |      |
| Pitch                    | p     |         | .050 |      |             | 1.27 |      |
| Overall Height           | A     | .053    | .061 | .069 | 1.35        | 1.55 | 1.75 |
| Molded Package Thickness | A2    | .052    | .056 | .061 | 1.32        | 1.42 | 1.55 |
| Standoff §               | A1    | .004    | .007 | .010 | 0.10        | 0.18 | 0.25 |
| Overall Width            | E     | .228    | .237 | .244 | 5.79        | 6.02 | 6.20 |
| Molded Package Width     | E1    | .146    | .154 | .157 | 3.71        | 3.91 | 3.99 |
| Overall Length           | D     | .189    | .193 | .197 | 4.80        | 4.90 | 5.00 |
| Chamfer Distance         | h     | .010    | .015 | .020 | 0.25        | 0.38 | 0.51 |
| Foot Length              | L     | .019    | .025 | .030 | 0.48        | 0.62 | 0.76 |
| Foot Angle               | phi   | 0       | 4    | 8    | 0           | 4    | 8    |
| Lead Thickness           | c     | .008    | .009 | .010 | 0.20        | 0.23 | 0.25 |
| Lead Width               | B     | .013    | .017 | .020 | 0.33        | 0.42 | 0.51 |
| Mold Draft Angle Top     | alpha | 0       | 12   | 15   | 0           | 12   | 15   |
| Mold Draft Angle Bottom  | beta  | 0       | 12   | 15   | 0           | 12   | 15   |

\* Controlling Parameter  
 § Significant Characteristic

Notes:  
 Dimensions D and E1 do not include mold flash or protrusions. Mold flash or protrusions shall not exceed .010" (0.254mm) per side.  
 JEDEC Equivalent: MS-012  
 Drawing No. C04-057

## PRODUCT IDENTIFICATION SYSTEM

To order or obtain information, e.g., on pricing or delivery, refer to the factory or the listed sales office.

| <u>PART NO.</u>    | <u>X</u>                 | <u>/XX</u>   | <b>Examples:</b>  |
|--------------------|--------------------------|--|---|
| <b>Device</b>      | <b>Temperature Range</b> | <b>Package</b>   |   |
| Device:            | MCP6021                  | Single Op Amp  | a) MCP6021T-E/OT: Tape and Reel, Extended temperature, 5LD SOT-23.  |
|                    | MCP6021T                 | Single Op Amp<br>(Tape and Reel for SOT-23, SOIC, TSSOP, MSOP)                                     | b) MCP6021-E/P: Extended temperature, 8LD PDIP.                     |
|                    | MCP6021R                 | Single Op Amp  | c) MCP6021-E/SN: Extended temperature, 8LD SOIC.                    |
|                    | MCP6021RT                | Single Op Amp<br>(Tape and Reel for SOT-23)  | a) MCP6021RT-E/OT: Tape and Reel, Extended temperature, 5LD SOT-23. |
|                    | MCP6022                  | Dual Op Amp  | a) MCP6022-I/P: Industrial temperature, 8LD PDIP.                   |
|                    | MCP6022T                 | Dual Op Amp<br>(Tape and Reel for SOIC and TSSOP)  | b) MCP6022-E/P: Extended temperature, 8LD PDIP.                     |
|                    | MCP6023                  | Single Op Amp w/ $\overline{CS}$   | c) MCP6022T-E/ST: Tape and Reel, Extended temperature, 8LD TSSOP.   |
|                    | MCP6023T                 | Single Op Amp w/ $\overline{CS}$<br>(Tape and Reel for SOIC and TSSOP)                             | a) MCP6023-I/P: Industrial temperature, 8LD PDIP.                   |
|                    | MCP6024                  | Quad Op Amp  | b) MCP6023-E/P: Extended temperature, 8LD PDIP.                     |
|                    | MCP6024T                 | Quad Op Amp<br>(Tape and Reel for SOIC and TSSOP)  | c) MCP6023-E/SN: Extended temperature, 8LD SOIC.                    |
| Temperature Range: | I                        | = -40°C to +85°C   | a) MCP6024-I/SL: Industrial temperature, 14LD SOIC.                 |
|                    | E                        | = -40°C to +125°C  | b) MCP6024-E/SL: Extended temperature, 14LD SOIC.                   |
| Package:           | OT                       | = Plastic Small Outline Transistor (SOT-23), 5-lead<br>(MCP6021, E-Temp; MCP6021R, E-Temp)         | c) MCP6024T-E/ST: Tape and Reel, Extended temperature, 14LD TSSOP.  |
|                    | MS                       | = Plastic MSOP, 8-lead<br>(MCP6021, E-Temp)  |   |
|                    | P                        | = Plastic DIP (300 mil Body), 8-lead, 14-lead  |   |
|                    | SN                       | = Plastic SOIC (150mil Body), 8-lead   |   |
|                    | SL                       | = Plastic SOIC (150 mil Body), 14-lead   |   |
|                    | ST                       | = Plastic TSSOP, 8-lead<br>(MCP6021, I-Temp; MCP6022, I-Temp, E-Temp;<br>MCP6023, I-Temp, E-Temp;) |   |
|                    | ST                       | = Plastic TSSOP, 14-lead   |   |