

PART NUMBER: 155MWR250K

METALLIZED POLYESTER WRAP AND FILL AXIAL LEAD CAPACITORS

Parts are RoHS compliant

Date code when parts became RoHS: 14



ELECTRICAL SPECIFICATIONS

Capacitance: 1.5 μ F

Dissipation Factor: 0.01 Max at 1000 Hz and 25°C

Temperature Coefficient: 400 PPM/°C: -200 PPM/°C, 200 PPM/°C

Ripple Current: - at - and 0

ESR: - at - and -

Self Inductance: 1 Nanohenries maximum per mm of body length and lead length

dvdt: 4 V/ μ s

Terminal to Terminal Dielectric strength: 1.6 times the rated DC voltage when applied between the terminals for 2 seconds

Insulation Resistance (Terminal to Terminal): 10000

Megohm \times Microfarads MINIMUM after Volts DC is applied for seconds at

Reliability: 3 FIT

Load Life: 2000 hours at 85°C with 125% of rated voltage

Capacitance Change: \leq 5% of initially measured value

D.F. Change: \leq 200% of maximum specified value

I.R. Change: $>$ 50% of minimum specified value

Tolerance: -10 % , +10 %

Temperature Range: -55°C to +125°C

Above 85°C the rated (DC/AC) voltage must be derated at per 1.25%/°C

WVDC: 250 Volts DC

SVDC: N/A Volts DC

VAC: 160 Volts AC

Terminal to case Dielectric strength: 200 times the rated DC voltage when applied between the terminals for 2~5 seconds

Insulation resistance (Terminal to Case): N/A Megohms MINIMUM after Volts DC is applied for seconds at

PHYSICAL DIMENSIONS

Diameter (D): 12.5 mm, MAX mm


Length (L): 29 mm, MAX mm

Lead Finish: Matte Tin

Lead Spacing (S): mm, +/- mm

Lead Diameter (d): 0.8 mm, +/-0.05 mm

Lead Length (LL): 35mm, +/- MIN mm



3757 W. Touhy Ave. Lincolnwood, IL 60712 (847)-675-1760 FAX (847)-673-2850
Illinois Capacitor (HK) Ltd., Tel: 85227930931, Fax: 85227930731, www.ilcap.com.hk
© 2009 Illinois Capacitor