


## SHC1027 -- Straight Male Cord Connectors



Machined Aluminum

Machined Aluminum

### Product Specifications

<p><b>Product Type</b></p>	 <p><b>Accessories</b></p>
<p><b>Accessory Item</b></p>	<p>Straight Male Cord Connectors</p>
<p><b>NPT Size</b></p>	<p>1/2" NPT</p>
<p><b>Cord Crip Cable Range</b></p>	<p>.63"-.75"</p>
<p><b>Material</b></p>	<p>Machined Aluminum</p>
<p><b>Ingress Protection</b></p>	<p>IP66</p>
<p><b>Operating Temperature</b></p>	<p>-40° F to 300° F (-40° C to 149° C)</p>
<p><b>Hazardous Locations</b></p>	<p>Hubbell cord connectors are suitable for use in hazardous locations per Class I Div. 2, Class II Div. 1 &amp; 2, Class III Div. 1 &amp; 2 in accordance with the NEC.</p>
<p><b>Certifications</b></p>	<p>UL Listed in Accordance with Standard 514B, CSA Certified, United States Coast Guard Approved, Title 46-Part 111</p>
<p><b>M Drawings</b></p>	<p><a href="#">Click here for M-Drawing</a></p>
<p><b>Brochures</b></p>	<p><a href="#">Click here for product brochure</a></p>
<p><b>Catalog Page</b></p>	<p><a href="#">Click here for catalog page G74</a></p>

<b>Catalog Section</b>	<a href="#">Click here for Section-G</a>
<b>UPC Number</b>	78358520027
<b>Weight in LBs</b>	0.15

