XVC6B15SK

Lens Unit Assembly , Steady or Flashing Light (Integral LED) with buzzer



Technical Characteristics

Approvals	UL Recognized - CE Marked
Enclosure Rating	NEMA 3R/12 - IP 54
Signal Color	Red
Supply Voltage	24V
Signaling Effect	Steady or Flashing Light (Integral LED) with buzzer
Mounting Type	Base
Size	Ø 60mm
Terminal Type	Pre-Wired
Туре	XVC

Shipping and Ordering

Discount Schedule XV GTIN 00785901706915 Package Quantity 1 Weight 0.98 lbs. Availability Code Stock Item: This item is normally stocked in our distribution facility. Returnability Y Country of Origin JP	Category	22617 -
Package Quantity 1 Weight 0.98 lbs. Availability Code Stock Item: This item is normally stocked in our distribution facility. Returnability Y	Discount Schedule	XV
Weight 0.98 lbs. Availability Code Stock Item: This item is normally stocked in our distribution facility. Returnability Y	GTIN	00785901706915
Availability Code Stock Item: This item is normally stocked in our distribution facility. Returnability Y	Package Quantity	1
Returnability Y	Weight	0.98 lbs.
·	Availability Code	Stock Item: This item is normally stocked in our distribution facility.
Country of Origin JP	Returnability	Υ
, •	Country of Origin	JP

document.

Generated: 03/16/2011 15:43:28

