

 Select Your Country/Region 




[Search](#)
[Home](#)[Products](#)[Support](#)[Services](#)[Selectors](#)[How to Buy](#)

Personal Surge Arrest 7 Outlet w/Tel 120V

Surge Protection for Personal Computers and Electronic Equipment.

Includes: 1.8 Meter Tel Cable (2), User Manual

Part Number : **PER7T**

-  [Compare Models](#)
-  [Email Technical Specifications](#)
-  [Printer Friendly](#)



[+] More Images

Additional Information


- [Product Overview](#)
- [User Manual & Installation Guides](#)
- [Product Distribution](#)

Technical Specifications

Output

Number of Outlets	7
Receptacle Style	NEMA 5-15R

Input

Nominal Input Voltage	120V
Input Frequency	50/60 Hz +/- 5 Hz (auto sensing)
Input Connections	NEMA 5-15P 
Maximum Line Current per phase	15A

Features:

- i Catastrophic Event Protection
- i Data-line Protection
- i Lightning and Surge Protection
- i Protection working indicator
- i Site wiring fault indicator

Surge Protection and Filtering

Surge energy rating	240 Joules
eP Joule Rating	1060
EMI/RFI Noise rejection (100 kHz to 10 mHz)	60 dB
Peak Current Normal Mode	6.50 kAmps
Peak Current Common Mode	13 kAmps
Dataline protection	RJ-11 Modem/Fax/DSL protection (two wire single line)
Data Lines Protected (multi-line only)	1
Let Through Voltage Rating	< 300

Physical

Net Weight	1.80 lbs. (0.82 kg)
Maximum Height	2.00 inches (51 mm)

Maximum Width	4.25 inches (108 mm)
Maximum depth	10.50 inches (267 mm)
Shipping Weight	2.30 lbs. (1.05 kg)
Shipping Height	2.10 inches (53 mm)
Shipping Width	7.25 inches (184 mm)
Shipping Depth	12.75 inches (324 mm)
Master Carton Units	12.00
Master Carton Weight	27.80 lbs.
SCC Codes	10731304000126
Color	Beige
Units per Pallet	384.00

Environmental

Operating Environment	0 - 40 °C (32 - 104 °F)
Operating Relative Humidity	0 - 95%
Operating Elevation	0-10000 feet (0-3000 meters)
Storage Temperature	-15 - 45 °C (5 - 113 °F)
Storage Relative Humidity	0 - 95%
Storage Elevation	0-50000 feet (0-15000 meters)

Conformance

Regulatory Approvals	CSA,UL 497A,UL 1283,UL 1363,UL 1449
Standard Warranty	Lifetime
UL 1449 TVSS Rating	330 V

[Copyright](#) © American Power Conversion Corp., all rights reserved
[About APC](#)[Investors](#)[Job Seekers](#)[Press](#)[Feedback](#)[Contact](#)[Privacy Policy](#)