



List Price \$92.00 USD

Availability **Stock Item: This item is normally stocked in our distribution facility.****Technical Characteristics**

Actuation	Vertical - One Way
Actuator	Thermoplastic Roller Lever Plunger (ZCE27)
Head Type	Top Plunger
Roller Dimension	14 x 5.5mm
Operating Torque/Force	53 Inch-Pounds (6Nm)
Actuator Action	Momentary
Lever Arm Length	41mm
Repeat Accuracy	0.1mm (on the tripping points)
Maximum Actuation Speed	1 m/s
Conforming to Standards	GENELEC EN 50047
Type	XCKP
RoHS	Yes
Type of Duty	General Duty
Body Type	Compact Modular (ZCP21)
Shock Resistance	50G
Body Material	Plastic
Vibration Resistance	25G
Connection Type	Conduit Entrance (0.5" NPT)
Weight	0.220 lbs (0.100kg)
Contact Configuration	1 N.O./1 N.C.
Contact Operation	Snap Action
Positive Opening	Yes
Terminal Type	Screw Clamp
Ampere Rating	10A
Marketing Trade Name	OsiSense
Maximum Voltage Rating	240VAC/250VDC
NEMA Enclosure Rating	NEMA 1/2/4/6/12/13
Degree of Protection	IP66/67
Operating Temperature Range	-13 to 158°F (-25 to 70°C)
Approvals	UL Listed - CSA Certified - CE Marked

Shipping and Ordering

Generated: 07/13/2010 15:20:25

Category	22418 - Limit Switches, Medium Duty, Compact, IEC, Type XCKP & XCKT
Discount Schedule	T
GTIN	00785901269625
Package Quantity	1
Weight	0.23 lbs.
Availability Code	Stock Item: This item is normally stocked in our distribution facility.
Returnability	Y
Country of Origin	MX

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.

Generated: 07/13/2010 15:20:25