

0548	8975	3016	9548
<b>0548-0-15-XX-21-XX-10-0</b> Solder mount in .036 min. mounting hole	<b>8975-0-15-XX-21-XX-10-0</b> Solder mount in .036 min. mounting hole	<b>3016-0-15-XX-21-XX-10-0</b> Solder mount in .036 min. mounting hole	<b>9548-0-15-XX-21-XX-10-0</b> Solder mount in .036 min. mounting hole

8637	1407	0553/8553
<b>8637-0-15-XX-21-XX-10-0</b> Solder mount in .037 min. mounting hole	<b>1407-0-15-XX-11-XX-10-0</b> Solder mount in .040 min. mounting hole	<b>X553-X-15-XX-X1-XX-10-0</b> Hex press-fit in .041 plated thru hole

Basic Part Number	Length L	Depth N
0553-1	.140	.124
0553-2	.170	.154
0553-3	.282	.266
8553-0	.245	.229

0566	0442	0554
<b>0566-X-15-XX-21-XX-10-0</b> Solder mount in .039 min. mounting hole	<b>0442-0-15-XX-11-XX-10-0</b> Solder mount in .040 min. mounting hole	<b>0554-0-15-XX-21-XX-10-0</b> Solder mount in .040 min. mounting hole

Basic Part Number	Length L
0566-1	.083
0566-2	.138

<p><b>SPECIFICATIONS</b></p> <p><b>SHELL MATERIAL:</b> Brass Alloy 360, 1/2 Hard</p> <p><b>CONTACT MATERIAL:</b> Beryllium Copper Alloy 172, HT</p> <p><b>DIMENSION IN INCHES TOLERANCES ON:</b> LENGTHS: ±.005 DIAMETERS: ±.002 ANGLES: ± 2°</p>	<p><b>ORDER CODE: XXXX - X - 15 - XX - XX - XX - 10 - 0</b></p> <p><b>BASIC PART #</b> →</p> <p><b>SPECIFY SHELL FINISH:</b></p> <p>01 200µ" TIN/LEAD OVER NICKEL</p> <p>80 200µ" TIN OVER NICKEL ◊</p> <p>15 10µ" GOLD OVER NICKEL ◊</p> <p><b>SPECIFY CONTACT FINISH:</b></p> <p>02 100µ" TIN/LEAD OVER NICKEL</p> <p>84 100µ" TIN OVER NICKEL ◊</p> <p>27 30µ" GOLD OVER NICKEL ◊</p> <p align="center"><b>SELECT CONTACT</b> #11 or #21 CONTACT (DATA ON PAGE 217)</p>
---	--

