RG59B Coaxial Cable, BNC Male / Male, 4.0 ft

Features for this product

- 75 Ohm video signal transmission
- True 75 Ohm BNC eliminates interface impedance mismatch
- RG59B/U solid center conductor minimizes insertion loss
- Crimp style attachment and molded strain relief result in a highly durable assembly
- Available from stock in 19 lengths ranging from .5 to 200 feet



When you need a well built, durable RG59B/U cable assembly with true 75 Ohm BNC male connectors and you need it now we have your cable assembly in stock. We offer these highly popular 75 Ohm coaxial cable assemblies with molded strain reliefs for maximum durability. In addition our true 75 Ohm BNC connectors feature gold plated center contacts for minimal attenuation and nickel plated bodies for enhanced corrosion resistance. We typically stock these cables in a multiple of standard lengths from .5 ft to 200 ft. We are sure to have just the length you are looking for in stock ready for immediate delivery.

Details for this Coaxial product		
L-com Item #	CC59B-4	
Manufacturer	L-com	
UPC #	822335006560	
RoHS Status	RoHS Compliant ⊘	

L-com CONNECTIVITY PRODUCTS

Item #	Description						
RG59A/U	*	Center Conductor: 22 (7x30) AWG bare		MINAL ATTEN		En la	
	Ø.240 in. Nominal	compacted copper • Shielding: Bare copper braid (96% coverage)	MHz 50	db/100 ft 2.1	db/100m 6.9		
	Nominal	 Insulation: Foam polyethylene Jacket: Black PVC 	100 200	3.0 4.5	9.8 14.8		
75 Ohm Imped	dance	Operating Temperature: -40°C - +80°C	400 1000	6.6 10.9	21.7 35.8		
RG59A/U - 75 Ohn	n Coaxial Cables	with Inline BNC to Type F Plug BNC Male / Type F Male, 1.0 ft					CC59A-BF
CC59A-BF-3 CC59A-BF-6	RG59A Cable,	BNC Male / Type F Male, 1.0 ft BNC Male / Type F Male, 3.0 ft BNC Male / Type F Male, 6.0 ft					
CC59A-BF-9 CC59A-BF-12	RG59A Cable,	BNC Male / Type F Male, 9.0 ft BNC Male / Type F Male, 12.0 ft					
RG59A/U - 75 Ohn	n Coaxial Cables	with Two Type F Plugs					
OCF59-1 OCF59-3	RG59A Cable,	Type F Male / Male, 1.0 ft Type F Male / Male, 3.0 ft					
OCF59-6 OCF59-9 OCF59-12	RG59A Cable,	Type F Male / Male, 6.0 ft Type F Male / Male, 9.0 ft Type F Male / Male, 12.0 ft					
OCF59-25 OCF59-50	RG59A Cable,	Type F Male / Male, 25.0 ft Type F Male / Male, 25.0 ft					CCF59
CCF59-100	RG59A Cable,	Type F Male / Male, 100.0 ft					
CCF59-MF-1	RG59A Cable,	with One Inline Type F Plug and One Type F Bul Type F Male / Female, 1.0 ft	khead Ja	CK			
CCF59-MF-6 CCF59-MF-12	RG59A Cable,	Type F Male / Female, 6.0 ft Type F Male / Female, 12.0 ft					
CCF59-MF-25 CCF59-MF-50		Type F Male / Female, 25.0 ft Type F Male / Female, 50.0 ft					
RG59A/U - 75 Ohn CC59A-RR-1	n Coaxial Cables	with Two Inline RCA Plugs RCA Male / Male, 1.0 ft					
CC59A-RR-3 CC59A-RR-6	RG59A Cable,	RCA Male / Male, 3.0 ft RCA Male / Male, 6.0 ft					CCF59-MF
0C59A-RR-9 0C59A-RR-12	RG59A Cable,	RCA Male / Male, 9.0 ft RCA Male / Male, 12.0 ft				() and	
	n Coaxial Cables	with Inline RCA to Inline BNC Plug				100	
CC59A-RB-1 CC59A-RB-3	RG59A Cable,	RCA Male / BNC Male, 1.0 ft RCA Male / BNC Male, 3.0 ft					
<u>CC59A-RB-6</u> <u>CC59A-RB-9</u>	RG59A Cable,	RCA Male / BNC Male, 6.0 ft RCA Male / BNC Male, 9.0 ft					
CC59A-RB-12 BG59A/LL - 75 Ohn		RCA Male / BNC Male, 12.0 ft with Inline RCA to Type F Plug					
OC59A-RE-1 OC59A-RE-3	RG59A Cable,	RCA Male / Type F Male, 1.0 ft RCA Male / Type F Male, 3.0 ft					CC59A-RR
CC59A-RF-6 CC59A-RF-9	RG59A Cable,	RCA Male / Type F Male, 6.0 ft RCA Male / Type F Male, 9.0 ft					
CC59A-RF-12	RG59A Cable,	RCA Male / Type F Male, 12.0 ft					in l
L-com offers a wide var	riety of RG59B/U cable	with Molded BNC Plugs assemblies utilizing BNC and Type F connectors. RG59B/U cat					
Type F connector featur	es a captivated gold p	L-com offers right angle and female bulkheads. All connector lated center pin for enhanced performance. The solid center of the solid center of the solid center of					
optimum insertion loss p	performance.		NO	MINAL ATTEN			
RG59B/U	¥	 Center Conductor: 22 AWG solid bare copper covered steel 	MHz	db/100 ft	db/100m		CC59A-RB
	Ø.242 in. Nominal	 Shielding: Bare copper braid (95% coverage) Insulation: Polyethylene 	50 100	2.4 3.4	7.9 11.1		
		Jacket: Black PVC	200 400	4.9 7.0	16.1 23.0		
75 Ohm Imped		Operating Temperature: -40°C - +80°C	1000	12.0	39.3	and the	
		les with Two Inline BNC Plugs					
<u>CC59B-05</u> <u>CC59B-1</u> <u>CC59B-1.5</u>	RG59B Cable,	BNC Male / Male, 0.5 ft BNC Male / Male, 1.0 ft BNC Male / Male, 1.5 ft					
<u>CC59B-2</u> CC59B-2.5	RG59B Cable,	BNC Male / Male, 2.0 ft BNC Male / Male, 2.5 ft					CC59A-RF
CC59B-3 CC59B-4	RG59B Cable,	BNC Male / Male, 3.0 ft BNC Male / Male, 4.0 ft					00004 11
CC59B-5 CC59B-6	RG59B Cable,	BNC Male / Male, 5.0 ft BNC Male / Male, 5.0 ft					
CC59B-7.5 CC59B-10	RG59B Cable,	BNC Male / Male, 7.5 ft BNC Male / Male, 10.0 ft				mi	
OC59B-12 OC59B-15	RG59B Cable, RG59B Cable,	BNC Male / Male, 12.0 ft BNC Male / Male, 15.0 ft					
CC59B-25 CC59B-50	RG59B Cable,	BNC Male / Male, 25.0 ft BNC Male / Male, 50.0 ft				put -	
OC59B-75 OC59B-100	RG59B Cable,	BNC Male / Male, 75.0 ft BNC Male / Male, 100.0 ft				THE LOW	CC59B
CC59B-150 CC59B-200		BNC Male / Male, 150.0 ft BNC Male / Male, 200.0 ft				10 - 8ª	
						* *	