



S84Z-401



S84Z-90



S84A-410



S82A-310



S84A-310

CLASS 2 TRANSFORMERS – ENERGY LIMITING

Various Standard Configurations of Step Down Transformers Designed to Power 24V AC Control Systems

FEATURES

- Energy limiting design, unaffected by momentary short circuit.
- Continued short circuit of secondary will cause primary winding to open in 1 to 2 minutes without creating a fire hazard.
- Maximum ambient temperature is 150°F.

SPECIFICATIONS

Agency U.L. listed

SKELETON TYPE WITH VERTICAL & HORIZONTAL CHANNEL FRAMES FOR MOUNTING

Model Number	Primary to Secondary Voltages	Output Rating	Terminations	
			Line	Load
S84Z-401	120/208/240v to 25v 60Hz	40 VA	12" leads	12" leads

UNIVERSAL MOUNTED TYPES (Plate, Foot or Hub Mount)

Model Number	Primary to Secondary Voltages	Output Rating	Terminations	
			Line	Load
S84-11	120v to 25v 60Hz	40 VA	10" leads	Screw terminals
S84Z-90	120/208/240v to 25v 60Hz	40 VA	10" leads	Screw terminals

PLATE MOUNTED TYPES

Model Number	Primary to Secondary Voltages	Output Rating	Terminations	
			Line	Load
S81-125	120v to 25v 60Hz	40 VA	10" leads	Screw terminals
S84A-410	Same as S81-125 except transformer recessed in plate and U.L. recognized.			

HUB MOUNT Class 2 Not Wet/Class 3 Wet (C.S.A. Certified and U.L. Listed)

Model Number	Primary to Secondary Voltages	Output Rating	Terminations	
			Line	Load
*S82A-310	120v to 25v	20 VA	10" leads	Screw/spade terminals

UNIVERSAL MOUNTED TYPES (Plate, Foot or Hub Mount)

Class 2 Not Wet/Class 3 Wet (C.S.A. Certified and U.L. Listed)

Model Number	Primary to Secondary Voltages	Output Rating	Terminations	
			Line	Load
*S84A-310	120v to 25v	40 VA	10" leads	Screw/spade terminals

* Indicates Canadian Model Number: call 1-800-305-6953 to order