

## SBCHE61R5K Product Details



Documentation & Additional Information	
Product Drawings: • None Available	Additional Information: • Product Line Information
Catalog Pages/Data Sheets: • <u>High Power Resistor - Type SBC (Square Ceramic) Seri</u> (PDF, English)	Related Products: • <u>Tooling</u>
<ul> <li>Product Specifications:</li> <li>None Available</li> </ul>	
Application Specifications: • None Available	
Instruction Sheets: • None Available	
CAD Files: • None Available	
List all Documents	

Product Features (Please use the Product Drawing for all design activity)		
Product Type Features:         • Product Type = Fixed Resistor         • Resistor Type = Power Resistor         • Resistance ( $\Omega$ ) = 1.5         • Element = Wirewound         • Termination Type = Tinned Copper Leads         Electrical Characteristics:         • Resistance Selection ( $\Omega$ ) = <1K         • Power Rating (W) = 7.00         • Tolerance (%) = 10	<ul> <li>Industry Standards:         <ul> <li><u>RoHS/ELV Compliance</u> = RoHS compliant, ELV compliant</li> <li><u>Lead Free Solder Processes</u> = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C</li> <li>RoHS/ELV Compliance History = Converted to comply with RoHS directive</li> </ul> </li> <li>Conditions for Usage:         <ul> <li><u>Temperature Coefficient (ppm/°C)</u> = ±400</li> </ul> </li> </ul>	
<ul> <li>Package Type = Loose Piece - Box</li> <li>Body Related Features:         <ul> <li>Series = SBC</li> <li>Mount Style = Axial Leaded</li> <li>Package, Component Size = 7 x 8 x 38</li> </ul> </li> </ul>	Operation/Application: • Application = Power Other: • Brand = CGS	