



[semiconductors](#)

[company](#)

[product](#)

[sales network](#)

[site index](#)

[contact us](#)

semiconductors :: product :: [General Purpose Rectifiers](#)

### Product: General Purpose Rectifiers

Product	Family	$I_{F(AV)}$ (A)	$I_{FSM}$ (A)	$V_{RRM}$ (V)	$V_F$ (V)	OUTLINE
<a href="#">FS1J</a>	FS1	1.0	30	600	1.1	DO214AC/SMA



## 1 Amp. Surface Mounted Glass Passivated Rectifier

<p><b>Dimensions in mm.</b></p>	<p><b>CASE:</b> SMA/DO-214AC</p>	<p><b>Voltage</b> 400 to 1200 V</p> <p><b>Current</b> 1.0 A</p>
		<ul style="list-style-type: none"> <li>• Glass passivated junction</li> <li>• High current capability</li> <li>• The plastic material carries U/L 94 V-0</li> <li>• Low profile package</li> <li>• Easy pick and place</li> <li>• High temperature soldering 260 °C 10 sec</li> </ul>
		<p><b>MECHANICAL DATA</b></p> <p>Terminals: Solder plated, solderable per IEC 68-2-20. Standard Packaging: 4 mm. tape (EIA-RS-481). Weight: 0.064 g.</p>

### Maximum Ratings and Electrical Characteristics at 25 °C

		FS1G	FS1J	FS1K	FS1M	FS1Q
Marking Code		R4	R5	R6	R7	R9
$V_{RRM}$	Maximum Recurrent Peak Reverse Voltage (V)	400	600	800	1000	1200
$V_{RMS}$	Maximum RMS Voltage (V)	280	420	560	700	840
$V_{DC}$	Maximum DC Blocking Voltage (V)	400	600	800	1000	1200
$I_{F(AV)}$	Forward current at $T_1 = 110\text{ °C}$	1.0 A				
$I_{FSM}$	8.3 ms. peak forward surge current (Jedec Method)	30 A				
$V_F$	Maximum Instantaneous Forward Voltage at 1.0A	1.1 V				
$I_R$	Maximum DC Reverse Current at Rated DC Blocking Voltage			1 $\mu$ A 50 $\mu$ A		
$t_{rr}$	Typical Reverse Recovery Time (0.5/1/0.25A)	1.8 $\mu$ s				
$C_j$	Typical Junction Capacitance (1MHz; -4V)	12pF				
$R_{th(j-l)}$ $R_{th(j-a)}$	Typical Thermal Resistance (5x5 mm <sup>2</sup> x 130 $\mu$ Copper Area)	27 °C/W 75 °C/W				
$T_j - T_{sig}$	Operating Junction and Storage Temperature Range	-55 to + 150 °C				