

[Home](#) > [Products](#) > [By Type](#) > [PolySwitch Resettable Devices](#) > [Product Feature Selector](#) > Product Details

TS600-170F-2 Product Details



TS600-170F-2

TE Part Number: D83387-000



[Active](#)

PolySwitch Resettable Devices



[Always EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

Product Highlights:

- Telecom Application
- Family Name = TS600
- Surface Mount Construction
- IH (Room Temperature) = .17 Amps.
- IT (Room Temperature) = .40 Amps.

[View all Features](#) | [Find Similar Products](#)

Documentation & Additional Information

Product Drawings:

- [TS600-170F](#) (PDF, English)

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)**Product Type Features:**

- UL Recognized = File No. E74889
- CSA File No. = 78165C
- Comment = Devices are available with 0.5 ohm resistance matching.; Designed for equipment required to meet Telcordia GR-1089, UL60950 and TIA968; can be used for ITU applications.

Electrical Characteristics:

- [IH \(Room Temperature\) \(Amps.\)](#) = 0.17
- [IT \(Room Temperature\) \(Amps.\)](#) = 0.40
- [Vmax Operating \(V\)](#) = 60
- [Rmin \(•\)](#) = 4.00
- [Rmax \(•\)](#) = 9.000
- [R1 Max \[Post Trip\] \(•\)](#) = 18.00
- [Vmax Interrupt \(V rms\)](#) = 600
- [UL Rated Current \(Amps.\)](#) = 3
- Tripped Power Dissipation (Typical) (W) = 2.50
- R (Typical) (•) = 9.00
- UL Rated Voltage (V) = 60

Termination Related Features:

- Construction = Surface Mount

Contact Related Features:

- Family Name = TS600

Configuration Related Features:

- Coating = Boxed

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Reflow solder capable to 245°C, Reflow solder capable to 260°C
- RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

- [Operating Temperature \(Max.\) \(°C\)](#) = 85

Operation/Application:

- Application = Telecom

Packaging Related Features:

- Packaging Method = Tape & Reel

Other:

- Brand = Raychem