



List Price \$196.00 USD

Availability **Stock Item: This item is normally stocked in our distribution facility.**

**Technical Characteristics**

Head Type	Top Plunger
Actuation	Horizontal
Actuator Action	Momentary
Lever Arm Length	n/a
Actuator	Steel Roller Lever Plunger (ZCE02)
Roller Dimension	0.46 x 0.13 Inches
Operating Torque/Force	7 Inch-Ounces (0.05Nm)
Maximum Actuation Speed	0.5 m/s
Degree of Protection	IP66/67/68
Repeat Accuracy	0.05mm (on tripping points)
Body Type	Miniature Modular (ZCMD21)
Body Material	Zinc Alloy
Operating Temperature Range	-13 to 158°F (-25 to 70°C)
Conforming to Standards	CENELEC EN 50047
RoHS	Yes
Positive Opening	Yes
Connection Type	PVR Cable (5m)
Type	XCMD
Shock Resistance	25G
Vibration Resistance	5G
Contact Configuration	1 N.O./1 N.C.
Contact Operation	Snap Action
Ampere Rating	6A
Maximum Voltage Rating	240VAC/250VDC
NEMA Enclosure Rating	NEMA 1/2/4X/6/6P/12/13
Weight	0.408 lbs (0.185kg)
Approvals	UL Listed - CSA Certified - CE Marked
Marketing Trade Name	OsiSense

**Shipping and Ordering**

Category	22435 - Limit Switches, Miniature, Type XCM
Discount Schedule	T

Generated: 07/13/2010 14:58:50

GTIN	00785901269519
Package Quantity	1
Weight	1.1 lbs.
Availability Code	Stock Item: This item is normally stocked in our distribution facility.
Returnability	Y
Country of Origin	MX

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.

Generated: 07/13/2010 14:58:50