



semiconductors

company

product

sales network

site index

contact us

semiconductors :: product :: [Bridge Rectifiers \(In Line\)](#)

### Product: Bridge Rectifiers (In Line)

Bridge Rectifiers are key devices in many applications where a rectifier signal is required as Input voltage. Linear Power Supplies, SMPS, Battery Chargers, Electronic Ballast... are some applications where they are used.

Manufactured using HYPERRECTIFIER® technology, we offer these devices in several different packages: SMD, Dual In Line, Round, In Line and Square Power.

Product	Family	$I_{F(AV)}$ (A)	$I_{FSM}$ (A)	$V_{RRM}$ (V)	$V_F$ (V)	OUTLINE
<a href="#">FBI4J5M1</a>	FB14-5M1	4.0	150	600	1.0	In line medium



## 4 Amp. Glass Passivated Bridge Rectifier

<p><b>Dimensions in mm.</b></p> <table border="1" style="margin-left: auto; margin-right: auto; border-collapse: collapse;"> <thead> <tr> <th>L</th> <th>suffix</th> </tr> </thead> <tbody> <tr> <td>17.5</td> <td></td> </tr> <tr> <td>8</td> <td>-4</td> </tr> </tbody> </table> <p><b>Plastic Case</b></p>	L	suffix	17.5		8	-4	<p style="text-align: center;"><b>Voltage</b> 50 to 1000 V.</p> <p style="text-align: center;"><b>Current</b> 4.0 A.</p> <div style="text-align: center; margin: 10px 0;"> </div> <ul style="list-style-type: none"> <li><b>Glass Passivated Junction Chips.</b></li> <li>UL recognized under component index file number E320541.</li> <li>Lead and polarity identifications.</li> <li>Case: Molded Plastic.</li> <li>Ideal for printed circuit board (P.C.B.).</li> <li>High surge current capability.</li> <li>The plastic material carries U/L recognition 94 V-O.</li> </ul>
L	suffix						
17.5							
8	-4						
<p><b>• Mounting Instructions</b></p> <ul style="list-style-type: none"> <li>High temperature soldering guaranteed: 260 °C – 10 sc.</li> <li>Recommended mounting torque: 8 Kg.cm.</li> </ul>							

### Maximum Ratings, according to IEC publication No. 134

		FBI4A 5M1	FBI4B 5M1	FBI4D 5M1	FBI4G 5M1	FBI4J 5M1	FBI4K 5M1	FBI4M 5M1
$V_{RRM}$	Peak recurrent reverse voltage (V)	50	100	200	400	600	800	1000
$V_{RMS}$	Maximum RMS voltage (V)	35	70	140	280	420	560	700
$I_{F(AV)}$	Max. Average forward current with heatsink without heatsink	4.0 A at 100 °C 3.0 A at 40 °C						
$I_{FSM}$	8.3 ms. peak forward surge current <small>(Jedec Method)</small>	150 A						
$I^2t$	Rating for fusing ( $t < 8.3$ ms.)	93 A <sup>2</sup> sec						
$V_{DIS}$	Dielectric strength (terminals to case, AC 1 min.)	1500 V						
$T_j$	Operating temperature range	– 55 to + 150 °C						
$T_{stg}$	Storage temperature range	– 55 to +150 °C						

### Electrical Characteristics at $T_{amb} = 25^\circ\text{C}$

$V_F$	Max. forward voltage drop per element at $I_F = 4$ A	1.0V
$I_R$	Max. reverse current per element at $V_{RRM}$	5 $\mu$ A
$R_{th(j-c)}$	MAXIMUM THERMAL RESISTANCE Junction-Case. With Heatsink.	5 °C/W
$R_{th(j-a)}$	Junction-Ambient. Without Heatsink.	22 °C/W