VA	ām	CO	Panel Mount Indicator, Non-Relampable Neon Technology Mounting Hole, Ø 0.380"				
			.50		Rot	1S	
All dimensions are in inches				Recommen	Recommended panel thickness: 0.030" to 0.250"		
6" leads with 1/2	2" strip are sta	ndard		Storage ten Ambient ter Voltage tole	mperature T _A : -20°C - +6		
Part No.		Lens Color	Voltage	Current mA	Rated Life		
Neon 115VAC	Series	<u> </u>					
WL-6010M1		Red	105-125VAC	1.5mA	25,000 Hrs		
WL-6010M3		Amber	105-125VAC	1.5mA	25,000 Hrs		
WL-6012M5		Green	105-125VAC	1.5mA	25,000 Hrs		
Neon 230VAC	Series						
WL-6011M1		Red	208-250VAC	1.5mA	25,000 Hrs		
WL-6011M3	1	Amber	208-250VAC	1.5mA	25,000 Hrs		
WL-6013M5		Green	208-250VAC	1.5mA	25,000 Hrs		
Body Material: Lens Material: Bezel Material:	Nylon, white Polycarbonate Stainless stee		Certifications:	Please contact Wa	icators carry Agency approvals. amco for the latest Agency information	ation	
Wire Gauge: 22 AWG Gaskets: Buna-N		regarding the specific product series and voltage required. Options: Additional options and lens styles available. Please contact Wamco for more information.					
Drawn	SC EB	03/01/10	Panel M	ount Indicators	Datasheet:	Re	
		1 112/111/11					
hecked pproved	EB	03/02/10		Neon	WL-601XMX Series	1	

11555 Coley River Circle Fountain Valley, CA 92708 714.545.5560 Fax: 714.545.6093