



FG2C-UA Function Generator

3 MHz Function Generator

- Square, Triangle, Sine waves, TTL and CMOS pulse outputs
- 0.3 Hz to 3 MHz range
- Variable controlled frequency (VCF) input
- Duty-cycle control
- Variable output
- 2 switchable 20 dB attenuators
- Variable DC offset control
- Includes line cords and fuses for either 117 V or 220 V operation

No hassle warranty

No waiting.

No shipping charges.



Our commitment to high-quality products and customer service is demonstrated by our industry exclusive "No Hassle" warranty. In the unlikely event that an Amprobe Test Tool requires warranty service, any of our local dealers are authorized to replace it, on the spot.

(note: \$500 MSLP limit)

This function generator provides a substantial array of output capabilities. It's extremely reliable for heavy day-to-day usage in electronic troubleshooting, production manufacturing test or as a breadboarding signal source.

The FG2C-UA function generator supplies all the basic test waveforms for fast, easy push-button selection of square, triangle and sine waves plus TTL or CMOS pulse output with low impedance, low distortion output. Smooth, analog knob dials frequency between 0.3 Hz and 3 MHz. Vary the output from less than 20mVp-p to 20Vp-p open circuit (10Vp-p max 50W load). Duty cycle control allows for setting pulses positive or negative. The VCF input allows external control for generating sweep signals.

Included Accessories

Test cables, spare fuses, 117 V line cord, 220 V line cord and users manual.

General Specifications

Power source	115 V ac or 230 V ac, $\pm 15\%$; 50/60 Hz
Operating environment	For indoor use, altitude up to 2000 m, 0 °C to 40 °C, 80 %RH
Storage environment	-10 °C to 70 °C @70 %R.H.
Dimensions (W x H x D)	243 mm x 93 mm x 292 mm (9.57 in x 3.66 in x 11.5 in)
Weight	2.0 kgs (4.4 lbs)
Safety approvals	EN61010-1, Cat. II, Pollution degree 2
Warranty	One-year

Specifications (at 23 °C; $\leq 70\%$ R.H.)

Function	Range	Accuracy
Main		
Frequency	0.3 Hz to 3 MHz (7 ranges)	$\pm 5\%$, + 1 Hz (@ 3.0 position)
Amplitude	> 10 Vpp (into 50 Ω load)	
Impedance	50 $\Omega \pm 10\%$	
Attenuator (knob)	-20 dB	± 1 dB
Attenuator (button)	-20 dB	± 1 dB
DC offset	< -5 V to > +5 V (into 50 Ω load)	
Duty-cycle control	80 %:20 %:80 % to 1 MHz; continuously variable	
Sine Wave		
Distortion	1 %, 0.3 Hz to 200 kHz THD < 35 dB below fundamental in all ranges (Specification applied from MAX. to 1/10 level)	
Flatness	< 0.3 dB, 0.3 Hz to 300 kHz; < 0.5 dB, 300 kHz to 3 MHz	
Triangle Wave		
Linear	$\geq 98\%$, 0.3 Hz to 100 kHz; $\geq 95\%$, 100 kHz to 3 MHz	
Square Wave		
Symmetry	$\pm 2\%$, 0.3 Hz to 100 kHz	
Rise or fall time	≤ 100 ns at maximum output (into 50 $\frac{1}{2}$ load)	
CMOS Output		
Level	4 Vpp	± 1 Vpp to 14.5 Vpp ± 0.5 Vpp adjustable
Rise or fall time	≤ 120 ns	
TTL Output		
Level	≥ 3 Vpp	
Fan out	20 TTL load	
Rise or fall time	≤ 25 ns	
VCF		
Input Voltage	-10 to +10	± 1 V (100:1)
Input Impedance	10 k Ω , $\pm 10\%$	

Amprobe® Test Tools
 website: www.Amprobe.com
 email: info@amprobe.com
 Everett, WA 98203
 Tel: 877-AMPROBE

Amprobe® Test Tools Europe
 In den Engematten 14
 79286 Glottertal, Germany
 Tel.: +49 (0) 7684 8009 - 0