

AC/DC Current Clamp-on Transducer

601C
602C



601C

601C

- The 601C extends the range of any DMM to measure AC/DC Amps to 1000 Amps
- Zero Adjust for DC Amps
- Jaw to 2.2 inches
- True RMS reading for AC current
- CAT II 1000V



602C

602C

- Measures AC Current to 400 Amps
- Jaw opening to 1.1 inches
- 1mV/A and 10mV/A current scale factors
- CAT II 600V
- Great for plant maintenance and HVAC
- Small sized and sturdy construction

SPECIFICATIONS

601C

Current Range DC: 1Amp to 1000Amps
Current Range AC: 1Amp to 1000Amps RMS
Scale Factor: 1mV/A
Accuracy: $\pm(3\% + 5d)$ AC and DC Amps
Working Voltage: 1000V Cat II
Power: 9 Volt battery
Operating Temperature: 0°C to 40°C (32° F to 104°F)
Storage Temperature: -10°C to 50°C (14°F to 122°F)
Jaw Size: 2.1 inches:
Size: 10"(L) x 4"(W) x 2"(D)
Weight: 1.1 lbs (520 grams)
Accessories: Hard carrying case and Operating manual

602C

Current Range DC: 0.1A to 400Amps RMS
Scale Factors: 1mV/A
10mV/A
Working Voltage: 600V CAT II
Operating Temperature: 0°C to 50°C (32°F to 122°F)
Storage Temperature: -20°C to 60°C (-4°F to 140°F)
Weight: 0.5 lb
Accessories: Soft carrying case and Operating manual