




## Proto-Type Boards

PSP-110001



383-K326 Shown

Dimensions: In.

### Specifications:

- Bus strip: 4 buses of 25 connected terminals are distributed in 4 rows
- Snap lock: easily combine to any size needed
- Base socket: twin columns are separated by 7.62mm center channel.  
There are 64 groups of 5-connected terminals on each side.
- Body: ABS Polymer (resists heat @ 90°C)
- Internal contact terminal: silver or gold plated silver alloy & nickel
- Resistance: <math><1\text{m}\Omega</math> @ 1KHz
- Back-plate: plastic stand

Mouser Stock No.	Base Socket	Bus Strip	Length (In.)	Width (In.)	Tie Points	5 Connected Terminals	25 Connected Buses	Binding Posts	IC Capacity 14 Pins	Weight (gm)
383-K158	2	3	7.598	6.772	1580	256	12	3	18	385
383-K242	3	4	7.559	10	2420	384	20	4	27	555
383-K326	4	5	9.724	10.748	3260	512	28	4	36	655

Updated: 5-11-05

383-K158, 383-K242, 383-K326

Available from Mouser Electronics

1-800-346-6873

www.mouser.com

Specifications are subject to change without notice. No liability or warranty implied by this information. Environmental compliance based on producer documentation.