

## KHX1600C9AD3/2G

### 2GB 256M x 64-Bit DDR3-1600MHz


### CL9 240-Pin DIMM

#### DESCRIPTION:

This document describes Kingston's 256M x 64-bit 2GB (2048MB) DDR3-1600MHz CL9 SDRAM (Synchronous DRAM) memory module, based on sixteen 128M x 8-bit DDR3 FBGA components. This module has been tested to run at DDR3-1600MHz at a low latency timing of 9-9-9-27 at 1.65V. The SPD is programmed to JEDEC standard latency DDR3-1333MHz timing of 9-9-9 at 1.5V. This 240-pin DIMM uses gold contact fingers and requires +1.5V. The JEDEC standard electrical and mechanical specifications are as follows:




#### FEATURES:

- JEDEC standard 1.5V  $\pm$  0.075V Power Supply
- VDDQ = 1.5V  $\pm$  0.075V
- 667MHz fCK for 1333Mb/sec/pin
- 8 independent internal bank
- Programmable CAS Latency: 5,6,7,8,9,10
- Posted CAS
- Programmable Additive Latency: 0, CL - 2, or CL - 1 clock
- Programmable CAS Write Latency(CWL) = 7(DDR3-1333)
- 8-bit pre-fetch
- Burst Length: 8 (Interleave without any limit, sequential with starting address "000" only), 4 with tCCD = 4 which does not allow seamless read or write [either on the fly using A12 or MRS]
- Bi-directional Differential Data Strobe
- Internal(self) calibration : Internal self calibration through ZQ pin (RZQ : 240 ohm  $\pm$  1%)
- On Die Termination using ODT pin
- Average Refresh Period 7.8us at lower then TCASE 85°C, 3.9us at 85°C < TCASE . 95°C
- Asynchronous Reset
- PCB : Height 1.180" (30.00mm), double sided component



#### PERFORMANCE:

- |  |                     |
|--|---------------------|
| <input checked="" type="checkbox"/> CL(IDD)  | 9 cycles            |
| <input checked="" type="checkbox"/> Row Cycle Time (tRCmin)                          | 49.5ns (min.)       |
| <input checked="" type="checkbox"/> Refresh to Active/Refresh Command Time (tRFCmin) | 110ns               |
| <input checked="" type="checkbox"/> Row Active Time (tRASmin)                        | 36ns (min.)         |
| <input checked="" type="checkbox"/> Power  | 1.800 W (operating) |
| <input checked="" type="checkbox"/> UL Rating  | 94 V - 0            |
| <input checked="" type="checkbox"/> Operating Temperature                            | 0° C to 85° C       |
| <input checked="" type="checkbox"/> Storage Temperature                              | -55° C to +100° C   |

**MODULE DIMENSIONS:**

**w/ Heat Sink Assembly**

