

Search by Keyword or Part #

353908-2 Product Details





353908-2

TE Internal Number: 353908-2





1.5mm AMP Mini CT Connectors

Always EU RoHS/ELV Compliant (Statement of ompliance)

Product Highlights:

- Connector Wire-to-Board, Wire-to-Board/Wire-to-Wire/Wire-to-Panel, Wire-to-Panel, Wire-to-
- Applies To Wire
- 1.50 mm Centerline Housing

View all Features











Documentation & Additional Information

Product Drawings:
• AMP MINI COMMON TERMINATED (CT) CONNECTOR 1.5mm PIT... (PDF, English)

Catalog Pages/Data Sheets:

- SENTATIVE TERMINALS AND CONNECTORS (PDF, English)
- PERSONAL SYSTEMS PRODUCTS (PDF, English)

- Product Specifications:

 AMP Mini Common Termination (CT) Connector 1.5mm Pit... (PDF, English)
 - AMP Mini CT Connector 1.5mm Pitch (Crimp Type), Lead... (PDF, Japanese)

Application Specifications:

• AMP MINI COMMON TERMINATION (CT) CONNECTOR, 1.5MM PI... (PDF, English)

Instruction Sheets:

- 1.5mm Pitch Mini CT DC Drawer Connector SF Type (PDF, Japanese)
 1.5mm Pitch Mini CT Hybrid Drawer Connector SF Type (PDF, Japanese)
- 1.5mm Pitch Mini CT Hybrid Drawer Connector Slim Type (PDF, Japanese)

CAD Files: (CAD Format & Compression Information) • 2D Drawing (DXF, Version B) • 3D Model (IGES, Version B)

- 3D Model (STEP, Version B)

List all Documents

Additional Information: • Product Line Information

Related Products:

- Tooling
 Mating Products (5)
- Contacts (2)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features: • Product Type = Connector

- Connector Type = Housing
- Termination Method to Wire/Cable = Crimp
- CSA File Number = LR 7189-133

Electrical Characteristics: Contact Current Rating (A) = 2

- Operating Voltage Reference = AC/DC
- Operating Voltage (V) = 50

Body Related Features: • Centerline (mm [in

- Centerline (mm [in]) = 1.50 [0.059]
- Number of Positions = 2
- Number of Rows = 1
- Length (X-Axis) (mm [in]) = 4.50 [0.1772]
- Width (Z-Axis) (mm [in]) = 3.60 [0.141] • Profile Height (Y-Axis) (mm [in]) = 6.00 [0.236]

Contact Related Features:

Contact Type = Socket

Housing Related Features: Housing Color = Nature

- Natural
- UL Flammability Rating = UL 94V-0

- Industry Standards:

 RoHS/ELV Compliance = RoHS compliant, ELV compliant
 - <u>Lead Free Solder Processes</u> = Not relevant for lead free process
 - RoHS/ELV Compliance History = Always was RoHS compliant
 - UL Rating = E28476

Conditions for Usage: • Applies To = Wire

- Operating Temperature (°C [°F]) = -30 +105 [-22 +221]
- Accepts Wire Insulation Diameter, Range (mm [in]) = 0.85 1.05 [0.0334 0.041]

- Operation/Application:

 Application Use = Wire-to-Board, Wire-to-Board/Wire-to-Wire/Wire-to-Panel, Wire-to-Panel, Wire-to-Wire
 - Pick and Place Cover = Without

Packaging Related Features: Packaging Method = Box

Other:
• Brand = AMP

🟮 BOOKMARK 📑 😭 🧦 ...

Corporate Information

Who We Are Investors

News Room Supplier Portal

Careers

Quick Links

Check Distributor Inventory Cross Reference

Find Documents & Drawings Product Compliance Support Center

Site Map

Customer Support

Email or Chat with Us Find a Phone Number Search Knowledge Base Manage Your Account

Sign up for our eNewsletter

Enter your email address



Follow Us On:







© 2010 Tyco Electronics All Rights Reserved | Privacy Policy

Provide Website Feedback